

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form No. 1004-0135
Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL NO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

SF 080536
6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO

10. FIELD AND POOL, OR WILDCAT

Lindrith Gallup Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

21-T25N-R3W

12. COUNTY OR PARISH 13. STATE

Rio Arriba NM

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Elliott Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 1355, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

600' FSL & 1980' FEL

14. PERMIT NO

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7340' GL 7352' KB

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Surface Casing & Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-25-88

MI&RU Four Corners Rig #14. Spud 12-1/4" surface hole at 11:15 am 7-24-88. Drilled to 845'. Surveys: 3/4 at 159', 3/4 at 314', 2 at 437', 2 at 598', 3/4 at 650', and 3/4 at 845'. Ran 19 jts 8 5/8" 24.0# ST&C casing measuring 800.05' and set at 833' KB. Ran Texas Pattern Guide Shoe, sawtoothed, insert bakelite baffle, and centralizer on 1st jt. and 19th jt. Rig up Western and cemented with 450 lb (531 cu ft) of Class "B", 2% calcium chloride, and 1/4 # ex Celoflake. Circulated cement to surface. Plug down 8:30 am 7-25-88.

RECEIVED
AUG 05 1988
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Harold W. Ellledge

TITLE

Petroleum Engineer

DATE

7-29-88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 02 1988

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

BY KH

