

## OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Missy	
9. Well No. 2	
10. Field and Pool, or Wildcat W Lindrith Gal/Dakota	
12. County Rio Arriba	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator  
HIXON DEVELOPMENT COMPANY

Address of Operator  
P.O. Box 2810, Farmington, New Mexico 87499

Location of Well  
UNIT LETTER K 1650' FEET FROM THE West LINE AND 1650' FEET FROM  
South LINE, SECTION 35 TOWNSHIP 25N RANGE 3W NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
7075' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
FORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PERMANENTLY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
REPAIR OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Drilling Progress

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded surface at 4:00 p.m. on August 30, 1988. Drilled 12-1/4" hole to 277'. Ran 257.35' of 9-5/8", 36#, 8rd, ST&C surface casing. Casing set at 272'. Cemented surface casing with 160 sks. (188 cu. ft.) of Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flake. WOC. Circulated cement to surface.

RECEIVED  
SEP 07 1988  
OIL CON. DIV.  
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

By Bruce E. Delventhal TITLE Petroleum Engineer DATE September 6, 1988

APPROVED BY ORIGINAL SIGNED BY ERNE DUSCH TITLE DEPUTY OIL & GAS INSPECTOR, DIST. #3 DATE SEP 12 1988

CONDITIONS OF APPROVAL, IF ANY: