

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1190' FSL, 1190' FWL, Sec. 20, T-24-N, R-6-W, NMPM

5. Lease Number
NMSF-078886

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

Canyon Largo Unit

8. Well Name & Number
Canyon Largo U #434

9. API Well No.
30-039-25402

10. Field and Pool
Basin Dakota

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

12-3-01 MIRU. ND WH. NU BOP. SDON.

12-4-01 TOOH w/204 jts 2 3/8" tbq. TIH w/5 1/2" csg scraper to 6363'. Blow well & CO. SDON.

12-5-01 TOOH. TIH w/5 1/2" cmt retainer, set @ 6346'. PT tbq to 1000 psi, OK. TOOH. Circ hole clean. Load csg w/112 bbl wtr. PT csg to 500 psi, OK. Plug #1: pump 21 sx Class "B" neat cmt inside csg on top of cmt retainer @ 6161-6346' to cover Dakota perfs. TOOH to 5283'. Plug #2: pump 19 sx Class "B" neat cmt inside csg @ 5115-5283' to cover Gallup perfs. TOOH to 3554'. Plug #3: pump 17 sx Class "B" neat cmt inside csg @ 3404-3554' to cover Mesaverde perfs. TOOH to 2013'. SDON.

12-6-01 Plug #4: pump 46 sx Class "B" neat cmt inside csg @ 1607-2013' to cover Fruitland & Pictured Cliffs perfs. TOOH to 1604'. Plug #5: pump 38 sx Class "B" neat cmt inside csg @ 1269-1604' Ojo Alamo & Kirtland. TOOH. PT bradenhead annulus to 500 psi, OK. TIH, perf 3 sqz holes @ 283'. Establish circ down csg & out bradenhead. Plug #6: pump 39 sx Class "B" neat cmt down csg & csg valve. Circ 1 bbl cmt to surface. TOOH. ND BOP. Cut off WH. Cmt fell 20' inside csg. Pump 10 sx Class "B" neat cmt to fill csg. Install dry hole marker w/5 sx Class "B" neat cmt. RD. Rig released.

Well plugged and abandoned 12-6-01.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 12/20/01
no

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any: