Førm approved. Budget Bureau No. 1004-0135 Form 3160-5 UNITED STATES

SUBMIT IN TRIPLICATE

(Other instructions on reverse side) Expires August 31, 1985 November 1983) Formerly 9-331) 5. LEASE DESIGNATION AND SERIAL NO. BUREAU OF LAND MANAGEMENT SF 078584 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME WELL X WELL 2. NAME OF OPERATOR S. PARM OR LEASE NAME McElvain Oil and Gas Properties, Inc. Federal A Com ADDRESS OF OPERATOR P.O. Box 2148, Santa Fe, NM 87504-2148

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 10. FIELD AND POOL, OR WILDCAT Ballard Pictured Cliffs 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 890' FNL & 1450' FEL Sec 13, T24N, R7W 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 12. COUNTY OR PARISH | 13. STATE 6933' GR <u>Rio Arriba</u> 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CARING SHOOT OR ACIDIZE SHOOTING OR ACIDIZING ABANDON MENT (Other) Set casing REPAIR WELL CHANGE PLANS (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) October 18, 1994 Run 62 joints of 4 1/2" 10.5 lb. J-55 ST&C casing. Total of 2569' set @ 2581' T.D. Centializers on string @ 1903', 1947', 2379', 2424', 2467' and 2511'. Cemented with 340 sx of 2% C-lite with 1/4 lb. celloflake added per sack. Followed with 120 sx Class B with 2% CaCL with 1/4 lb. celloflake added per sack. Circulated 40 good sacks of cement to surface. Plug down @ 4:15pm. Float held OK. Set 4 1/2" casing slips in wellhead with 32000 lb. Cut pipe off, released rig at 7:00pm. C. OIL COM. DIV.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY

CONDUCTIONS OF APPROVAL IF ANY.

CONDITIONS OF APPROVAL, IF ANY:

OCT 2 1994

DIST, R