

3160-5
(1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

Name of Operator
Elm Ridge Resources, Inc. (214) 696-8090

Address and Telephone No.
925 Greenville Ave., Ste. 1305, Dallas, Tx. 75206

Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface: **SWNE 17-24n-5w**

HL: Same

5. Lease Designation and Serial No.
BIA #69

6. If Indian, Allottee or Tribe Name
Jicarilla Apache

7. If Unit or CA, Agreement Designation
N/A

8. Well Name and No.
Apache #1

9. API Well No.
30-039-25608

10. Field and Pool, or Exploratory Area
Basin Dakota

11. County or Parish, State
Rio Arriba, NM

RECEIVED
MAY - 2 1997

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other **Completion**

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 3-28-97. Drill 12-1/4" hole to 354' KB. Ran 8 jts 8-5/8", 24#, K-55, STC surface casing, set @ 54' KB. Cemented with 200 sx Class B w/ 2% CaCl₂ + 1/4 #/sk Flocele. Drop plug and bump to 500 psi. Float held. Plug down @ 10:54 am 3-29-97.

Drilled 7-7/8" hole to 6977' KB. TD reached 9:00 am 4-10-97. Ran 209 jts 4-1/2", 11.6#, J-55, LTC production casing. Halliburton stage tool set @ 4855' KB. Cemented 1st stage w/ 705 sx 50/50 Poz w/ 1/4 #/sk Flocele + 2% gel + 4% Halad 344 + 5 #/sk Gilsonite. Displace with 107.6 bbl water. Bump plug. Float held. Open stage tool and circulate 2 bbl cement to surface. Circulate 4 hrs between stages. Cement 2nd stage w/ 920 sx Lite w/ 2% CaCl₂ followed w/ 85 sx Class B. Displace w/ 75.4 bbl water. Circulated 50 bbl cement to surface. Close stage tool. RD cementers. Set slips. Cut off casing. Release rig. Install wellhead.

cc: BIA, BLM (Albq. & SF), Elm (D&F), OCD (via BLM), Tribe

I hereby certify that the foregoing is true and correct.

Signed *Bruce Wood*

Title

Consultant (505) 466-8120

Date

4-30-97

(This space for Federal or State office use)

Approved by *Don R. [Signature]*
Conditions of approval, if any:

Title

Chief, Lands and Mineral Resources

Date

APR 30 1997

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side