n 3160-5 c 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM	i appro	OVED	
Budget Bur	cess No.	1004-013	5
Expires:	March	31, 1993	

5. Lease Designation and Serial No.

_	•		_		 	• • • •
	S	F	0	80421		

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name o not use this form for proposals to drill or to deepen or reentry to a different lesson Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE DEC - 5 1997 Canada Ojitos Unit Type of Well CHINI Well Well COUNT 8. Well Name and No. Other Name of Operator #45 (N-28) Benson-Montin-Greer Drilling Corp 9. API Well No. Address and Telephone No. 30-039-25713 4900 College Boulevard, Farmington, NM 10. Field and Pool, or Exploratory Area 87401 (505) 325-8874 Location of Well (Footage, Sec., T., R., M., or Survey Description) West Puerto Chiquito Mancos 500' FSL, 2200' FWL, Sec. 28, T25N, R1W, NMPM 11. County or Parish, State Rio Arriba, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Change of Plans Recompletion New Construction X Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/29/97

Ran 168 joints of 7 5/8", 26.4#, S-95, LT&C new casing. 6863.26' of casing set at 6854' (d.p. measurement). Howco stage collar at 3619' KB. Float collar at 6820' KB.

Cemented first stage with 185 sacks Halliburton lite with 10 pps gilsonite and 1/4 pps celloflake. Mixed at 12.7 ppg followed with 150 sacks class B with 1/4 pps celloflake and 0.3 1/2 HA322. Mixed at 15.6 ppg. Displace with 160 BBLS class B and 158 BBLS mud to displace cement to 6757'.

Cemented second stage with 275 sacks Howco lite with 10 pps gilsonite and 1/4 pps flocele. Mixed at 12.7 ppg and 1.84 cf/sack. Tailled in with 100 sacks class B with 1/4 pps flecele. Mixed at 15.6 ppg and 1.18 cf/sack. Displaced with 168 BBLS fresh water to close DV tool with 1500 psi.

I hereby certify the foregoing is true and confert		-	
Signed All Mile President	Date	11/17	197
Approved by 1 State office use)  Approved by 1 State office use)		DEC	4 1997
Approved by Conditions of approval, if any:	Date		1007

"itle 18 U.S.C. Section (001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.