For (I	Form 9-331 a (Feb. 1951)				

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Serica Pe
	U78914
Lease No.	
	Lindrith Unit
Unit	I-Sec. 713

SUBSCOUERT REPORT OF SHOOTING OR ACIDING NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Well No. 16 Is located 1050 ft. from Intention To SHOOTING OR ACIDIZE. SUBSCOURT REPORT OF ALTERING CASING.			SUBSEQUENT REPORT OF WATER SHUT-OFF
Well No. 16 is located 1050 ft. from Subscience of intention to respect to a color of intention to the part of the color of intention to the part of the color of intention to the part of the color of intention to the part of intention to the part of intention to the part of intention to part of intention to part of the part of intention to part of intention to adapt on the part of intention to part of intention to adapt on the part of par	NOTICE OF INTENTION TO DE	RILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
Subscouent report of re-drill or repair. Subscouent report of re-drill or report or re-drill or report or re-drill or report or re-	NOTICE OF INTENTION TO C	HANGE PLANS	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ADANDON WELL. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 1 19.57 Well No. 16 is located 1050 ft. from line and 1650 ft. from Well line of sec. 2 f. Well No. 2 ft. 10 is located 1050 ft. from line and 1650 ft. from Well line of sec. 2 f. Well Section 2 ft. 24	NOTICE OF INTENTION TO T	EST WATER SHUT-OFF	THE PART OF PERSON
Well No. 18 is located 1050 ft. from Willing and 1650 ft. from Willing of sec. 21 Well No. 18 is located 1050 ft. from Willing and 1650 ft. from Willing of sec. 21 Well No. 18 is located 1050 ft. from Willing and 1650 ft. from Willing of sec. 21 Well No. 18 is located 1050 ft. from Willing and 1650 ft. from Willing of sec. 21 Well No. 18 is located 1050 ft. from Willing and 1650 ft. from Willing of sec. 21 Will Sec and Sec. No.) (Twp.) (Range) (Mange) (Moridian) Wildcat Rio Arribe Now Mexico (Field) (County or Subdivision) (State or Terribry) The elevation of the derrick floor above sea level is 7003, ft. DETAILS OF WORK State names of and expected depths to objective sands; show alsea, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed overk) It is intended to plug and absolutenthis well in the following manuer. 1. Set cement plug from 3070 to 3200' with 50 sacks. 2. Set cement plug from 3070 to 3200' with 50 sacks. 3. Set cement plug from 3070 to 3200' with 100 anciss. 4. Set 4' x 4 pipe as marker. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commanced. Company El Paso Hetural Gas Company Address Box 997 Paraington, New Mexico By Paraington, New Mexico	NOTICE OF INTENTION TO R	E-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ABANDONMENT.
Well No. 16 is located 1650 ft. from William and 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William and 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William and 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William and 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 Well No. 16 is located 1650 ft. from William of sec. 21 It is intended to plug ft of above sea level is 7003 ft. DETAILS OF WORK State names of and expected depths to objective sands; show since, weights, and lengths of proposed casings; indicate mudding jobs, camentaring points, and all other important proposed werk) It is intended to plug from abondon this well in the full owing manner. 1. Set cement plug from 2550 to 2500' with 50 sacks. 2. Set cement plug from 2550 to 2500' with 106 sacks. 3. Set cement plug from 2550 to 2500' with 50 sacks. 4. Set 4' x 4' pipe as marker. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company Et Faso Setural Gas Company Farmington, Hew Mexico By Parmington, Hew Mexico By Parmin	NOTICE OF INTENTION TO SI	HOOT OR ACIDIZE	SUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) April 1	NOTICE OF INTENTION TO P	DANDON WELL	X
Well No. 18 is located 1050 ft. from line and 1650 ft. from Well line of sec. 21. Well Section 27 24M Ris Arribo (Range) (Ra	NOTICE OF INTENTION TO A		
Well No. 16 is located 1050 ft. from line and 1650 ft. from Wilcom Sec. 21		(INDICATE ABOVE BY CHECK MARK	K NATURE OF REPORT, NOTICE, OR OTHER DATA)
(V) Sec. and Sec. No.) (Yeld) (County or Subdivision) (Field) (County or Subdivision) (Field) (County or Subdivision) (State or Territory) (State			April 1 , 19 57
(Wese, and Sec. No.) (Wese, and Sec. No.) (Wese, and Sec. No.) (Range) (Wildcat (Rio Arribo (County or Subdivision) (State or Territory) (State or	Vell No. 16	is located 1650 ft. fron	n line and 1650 ft. from W line of sec. 27
(Yeld) (Yeld) (Range) (State or Territory) (State or Territory)	stronetim 27	248	B.M.F.M.
Wildcat (Field) (County or Subdivision) (State or Territory) (-		(Range) (Meridian)
(Field) (County or Subdivision) The elevation of the derrick floor above sea level is 7003 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) It is intended to plug and abandon this well in the following manuar. 1. Set cement plug from 3070 to 3200' with 50 sacks. 2. Set cement plug from 2556 to 2500' with 100 sacks. 3. Set cement plug from 130' to surface with 50 sacks. b. Set 4' x 4' pipe as marker. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Estural Gas Company Address Box 997 Farmington, New Mexico By Company Company Company Company Company By Company Compa		Rio Ar	
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) It is intended to plug and abandon this well in the following names. 1. Set cement plug from 3070 to 3200' with 50 sacks. 2. Set cement plug from 2550 to 2500' with 100 sacks. 3. Set cement plug from 130' to surface with 50 sacks. b. Set 4' x 4 pipe as marker. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Estaral Gas Company Address Box 997 Farmington, New Mexico By Control of F.W. 80YO		(County	or Subdivision) (State of Territory)
1. Set cement plug from 3070 to 3200' with 50 sacks. 2. Set cement plug from 2550 to 2800' with 100 sacks. 3. Set cement plug from 130' to surface with 50 sacks. 4. Set 4' x 4 pipe as marker. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Satural Gas Company Address Box 997 Parmington, New Mexico By OPERAL SET D. F. W. BOYD			
2. Set cement plug from 130' to surface with 50 sacks. b. Set 4' x 4 pipe as marker. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company El Paso Matural Gas Company Address Box 997 Parmington, New Mexico By Object 11 10 F W. 80YD		d depths to objective sands; show s ing points, and all	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- l other important proposed work)
Company Box 997 Address Farmington, New Mexico By Chick All Company By Chick All Co		d depths to objective sands; show s ing points, and all	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- l other important proposed work)
Address Box 997 Parmington, New Mexico By Opinion 1997 D. F. W. BOYD	It is intended 1. Set of the set	to plug and abandor ement plug from 3070 conent plug from 2550 ement plug from 130	this well in the following manner. this well in the following manner. to 3200' with 50 sacks. to 2500' with 100 sacks. to surface with 50 sacks.
Farmington, New Mexico By GOMMAN THE D. F. W. 80YD	It is intended 1. Set co 2. Set co 3. Set co b. Set 4	to plug and abandor to plug and abandor ement plug from 3070 ement plug from 2550 ement plug from 130 ' x h pipe as marke	this well in the following manner. O to 3200' with 50 sacks. O to 2500' with 100 sacks. I to surface with 50 sacks. I to surface with 50 sacks.
Parmington, New Mexico By Gold at 1987 D. F. W. 80YO	It is intended 1. Set co 2. Set co 3. Set co b. Set 4	to plug and abandor to plug and abandor ement plug from 3070 ement plug from 2550 ement plug from 130 ' x h pipe as marke	this well in the following manner. O to 3200' with 50 sacks. O to 2500' with 100 sacks. I to surface with 50 sacks. I to surface with 50 sacks.
	It is intended 1. Set ex 2. Set ex 3. Set ex b. Set 4 Lunderstand that this p	to plug and abandon to plug and abandon ement plug from 3070 ement plug from 2550 ement plug from 130 ' x 4 pipe as market plug of work must receive approval	this well in the following manner. O to 3200' with 50 sacks. O to 2500' with 100 sacks. I to surface with 50 sacks. I to surface with 50 sacks.
	1. Set con 2. Set con 3. Set con 4. Set 4. S	to plug and abandor to plug and abandor ement plug from 3070 ement plug from 2550 ement plug from 130 'x 4 pipe as market plus of work must receive approval	this well in the following samer. this well in the following samer. to 3200' with 50 sacks. to 2800' with 100 sacks. to surface with 50 sacks. In writing by the Geological Survey before operations may be commenced.

