



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Santa Fe**  
Lease No. **078883**  
Unit **Canyon Largo**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL..... <b>X</b>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**SEALY - GOVERNMENT #1-8**

**April 9**, 19**56**

Well No. **1-8** is located **990** ft. from **XXIX** line and **990** ft. from **E** line of sec. **8**

**SE/4, Section 8**  
(1/4 Sec. and Sec. No.)

**T-25N**  
(Twp.)

**R-6W**  
(Range)

**RCM**  
(Meridian)

**Wildcat**  
(Field)

**Rio Arriba**  
(County or Subdivision)

**New Mexico**  
(State or Territory)

**(Canyon Largo Unit)**

The elevation of the derrick floor above sea level is **6662** ft. (Estimated)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

**TD: 2600'**

Propose to run open ended drill pipe and equalize 55 sac cement @ 2600', pull to 2235' and equalize 75 sac cement. Place 10 sac cement in top of surface casing. Place a marker and clean up location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **THE SUPERIOR OIL COMPANY**

Address **MIDLAND, TEXAS**

By **L. J. Willis**

Title **Petroleum Engineer**