

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Petroleum Club, Inc.	8. Farm or Lease Name Turns Co.
3. Address of Operator Petroleum Club, Inc., Fairington, New Mexico	9. Well No. 2
4. Location of Well UNIT DEPTH 1110 FEET FROM THE OUTLINE AND 112 FEET FROM THE LINE, SECTION 1 TOWNSHIP 25 RANGE 25 NMPM.	10. Field and Pool, or Wildcat Indesignated (Shaded)
11. Elevation (Show whether DF, RT, GR, etc.) 270	12. County La Brea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-17-66 Drilled 3/4" hole to 3470' D. in 112 sts. (1110.74 feet) 2 7/8" casing equipped with regular pattern shoe, steel latch-in collar, three centralizers, and nine reciprocating scratchers. Set cas. at 3470' D., float collar at 3470' D., centralizers at 3319, 3259 and 3199, scratchers 3150-3258 and 3226-3196. Cemented with 250 # 50-50 port land cement sl. Set and 12 1/2" rods per sack. ~~TESTED~~ Tested cas. to 2500 gal. in 30 minutes before performing. Held 11.



14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE _____ DATE _____

Original Signed by A. R. Kendrick

PETROLEUM ENGINEER DIST NO. 3

SEP 29 1966

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____