

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Charles M
8. Well No. #3
9. Pool name or Wildcat Tapacito Pictured Cliffs
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 7284' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator Jack L. Cayais
3. Address of Operator 505-325-2627 C/O A-Plus Well Service, P.O. Box 1979, Farmington, NM 87401
4. Well Location Unit Letter L : 1850 Feet From The FSL Line and 790 Feet From The FEL Line Section 01 Township 25N Range 03W NMPM Rio Arriba County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 7284' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A-Plus Well Service, as contractor to the New Mexico Oil Conservation Division
(Contract No. 95-521.25-085), proposes to plug and abandon this well per the
attached procedure.

RECEIVED
DEC 23 1994
OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William F. [Signature] TITLE President DATE 12-20-94
TYPE OR PRINT NAME _____ TELEPHONE NO. _____

(This space for State Use)

APPROVED BY Johnny Robinson DEPUTY OIL & GAS INSPECTOR, DIST. #3 DATE DEC 23 1994
CONDITIONS OF APPROVAL, IF ANY:

WELL INFORMATION AND PLUGGING PROCEDURE

Invitation to Bid No.

OPERATOR JACK L. CAYIAS

WELL NAME CHARLES M #3

LOCATION L 01 25N 03W
unit sec. township range

FOOTAGE 1850/S; 790/E

COUNTY RIO ARRIBA

The information herein is taken from OCD well files. The bidder is responsible for obtaining all available data including a review of such files, on-site inspection and any other sources.

Failure to review available information will not justify for implementing supplemental rates or contract modification or

termination.

SUMMARY WELL DATA

SURFACE CASING: 8 5/8 @ 11' w/100 sks

INTERMEDIATE CASING: N/A

PRODUCTION CASING: 4 1/2 @ 3848' w/100 sks

TUBING: 2 3/8 @ unknown depth

OTHER INFORMATION:

PLUGGING PROCEDURE

including site preparation and cleanup

1. Install anchors and prepare location.
2. Rig up service unit. Blow down or kill well if necessary. Nipple down wellhead. Nipple up BOP and stripper head.
3. Pull and check tubing. If OK, may be used for work string.
4. Go in hole with tubing to PBTD @ 3848' and set a cement plug inside casing 3848-3450'. Pull out of hole to 3200' and reverse out tubing w/H²O. WOC 3 hours and tag up. If cement is in place, go to Step 5. If not, fill to 3450'.
5. Perforate casing at 2950'. Pump in and establish rate.
6. Set a cement retainer at 2800' and spot cement 2950-2800' in and outside casing. String out of retainer and dump 2 sacks on same.
7. Perforate casing at 200'. Tie onto casing and circulate cement to surface up the Bradenhead.
8. Set marker, fill pits, clean and level location.

RECEIVED
DEC 28 1984

OIL CORP. DIST. 3

Charles M #3

CURRENT

Tapacito Pictured Cliffs

SE Section 1, T-25-N, R-3-W, Rio Arriba County, NM

Today's Date: 11/1/94

Spud: 4/10/66

Completed: 10/1/66

Assumed
12-1/4" hole

8-5/8" 24.0#, Csg set @ 110'
Cmt w/100 sxs (Circulated to
Surface)

TOC @ 3189'
(Calc, 50%)

Pictured Cliffs Perforations:
3805' - 3834' 4/spf

Assume
7-7/8" hole

4-1/2" 10.5# set @ 3848',
Cmt w/100 sxs

TD 3848'