

(SUBMIT IN TRIPLICATE)

Indian Agency Dale, New Mexico

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Jicarilla Apache

Allottee Cont. #149-Tract #246

Lease No. J. Apache "7"

Sec-16	25N-R5W
--------	---------

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report for Setting 3 1/2"</u>	
	<u>Casing</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 20, 1963

Well No. 10 is located 1190' ft. from N line and 1980' ft. from W line of sec. 16

NE/4 Sec-16

25N

5W

100M

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Basin Dakota

Rio Arriba

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 6716' ft. -KB, 6714' ft. -DF.

FEB 25 1963

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

2-13-63 - 7428' Total Depth:

Set 3 1/2" OD 9.2#, 10RT, J55, R2, Non-Up Casing @ 7399', W/Hovee float shoe and Hovee Float Collar at 7337', W/Roto Scratchers & centralizers from 7335' to 7035', and Halliburton D. V. Tool @ 3911', Cemented First Stage in Dakota Zone with 275 Sacks 50/50 Pomix, W/12 1/2# Gilsomite per sack, mixed 4% Gel W/3/4% CFR2 and 100 Sacks 50/50 Pomix, no gel and 3/4% CFR2, Max. P. 2000#, Plug pumped down 11:15 AM, 2/13/63. Cemented by Halliburton.

Cemented second stage by Hallib. W/300 Sacks Class "C" Cement, mixed 6% Gel, thru D. V. Tool at 3911' (To cover Chasra & Pictured Cliffs Zones) Max. Press. Max. press. 1000#, pump plug to 3911'.

WOC

I understand that this plan of work must receive approval in writing by the Geological Survey before operations are to be commenced.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

PH-247-5353

By D.F. Furee

Title Production Foreman



