14. PERMIT NO.

## UNITED STATES SUBMIT IN TRIPLICATE\* DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

Form approved.
Budget Burgui No. 42-R1424.
5. Lease designation and serial no.

Section 7-24N-9W

New Mexico

12. COUNTY OR PARISE | 13. STATE

San Juan

GEOLOGICAL SURVEY	SF 078202-A
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different results ("APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTES OR TRIBE NAME
1.	7. UNIT AGREEMENT NAME
WELL X WELL OTHER	East Bisti Unit
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Skelly Oil Company	
3. ADDRESS OF OPERATOR	9. WELL NO.
1860 Lincoln Street, Denver, Colorado 80203	111
<ol> <li>LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)</li> </ol>	10. FIELD AND POOL, OR WILDCAT
At surface	Bisti Lower Gallup
	11. SEC., T., R., M., OR BLK, AND SURVEY OR AREA

6809' GR 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

1980' FNL & 660' FEL Section 7-24N-9W

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*	X	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CASING ABANDONMENT®
REPAIR WELL (Other)		CHANGE PLANS		(Other) (Note: Report results of mul Completion or Recompletion R	tiple completion on Well eport and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - 100' plug across Gallup Zone perfs. 5410-5446'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot

Third Plug - 150' plug extending downward from above Fruitland coal section across the Pictured Cliffs sand

Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo sand)

10 sacks of cement in top of surface casing with dry hole marker

	OH. pist. 3
18. I bereby certify that the foregoing is true and correct SIGNED	District Operations Supt. DATE June 8, 1971
(This space for Federal or State office use)	TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:	