## UNITED STATES SUBMER OF THE INTERIOR CONTRIBUTIONS ON THE INTERIOR CONTRIBUTION CONTRIBUTIONS ON THE INTERIOR CONTRIBUTION CON GEOLOGICAL SURVEY

SF	078556

	SUNDRY	NOTICES	AND	REPORTS	ON WELL
•.			1 . 111	4	• • • • • • • • • • • • • • • • • • •

	(Do not use this form for propos	als to drill or to deepen or plug back to TION FOR PERMIT—" for such proposal	n different reservoir.	1		
1.	CIL X CAS OTHER		OR COMPANY		7. UNIT AGREEMENT NAS East Bisti	
2.	Skelly Oil Company				B. FARM OR EXAME NAM	C
3.	Address of orerator 1860 Lincoln Street,	Denver, Colorado 80203			9. WELL NO. 94	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface				Bisti Lower Gallup		
1980' FSL & 1980' FEL Section 3-24N-10W					11. SEC., T., R., M., OR BUK. AND SURVEY OR AREA	
					Section 3-2	4N-10W
14	. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GF	R, etc.)		12. COUNTY OR PARISH	13. STATE
		6872' GR 6882' K	CB .		San Juan	New Mexico

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION	то:	SUBSEQUENT REPORT OF:		
	OR ALTER CASING PLE COMPLETE ON*  X	FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CASING ABANDONMENT*	
REPAIR WELL CHANG (Other)	E PLANS	(Other) (Note: Report results of multiple Completion or Recompletion Report	completion on Well and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIO proposed work. If well is directionally nent to this work.)

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - 100' plug across Gallup Zone perforations 5377-5430'

Second Plug - 50' inside the 5-1/2" casing and 50' above where casing is shot in two Third Plug - 150' cement plug extending downward from above the Fruitland Coal section across the Pictured Cliffs Sand

Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo Sand)

10 sacks of cement in top of surface casing with dry hole marker

	. /			
8. I hereby certify that the foreg	ing is true and correct			
SIGNED	Genly	TITLE District	Operations Supt.	DATE June 10, 1971
(This space for Federal or Sta	te office use)			
APPROVED BY		TITLE		DATE
CONDITIONS OF APPROVAL	IF ANY:			•