## (SUBMIT IN TRIPLICATE)

## UNITED STATES **DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY**

Land Office	Santa Fe
ease No.	080027
Jnit	

SUNDR	Y NOTICES A	AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHOT OFF
NOTICE OF INTENTION TO CHAN	GE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACTOINING
NOTICE OF INTENTION TO TEST	WATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DI	RILL OR REPAIR WELL	SUBSECUENT DEPOST OF DE DON'TIME OF DEPAIR
NOTICE OF INTENTION TO SHOO		A H O S GENERALIA SURVE
NOTICE OF INTENTION TO PULL		
NOTICE OF INTENTION TO ABAN		X
(IN	DICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
		August 30, , 19 5
/ell No. 1 is le	ocated 530 ft. from	m $N$ line and $K$ line of sec. $K$ line of sec. $K$ line of sec. $K$ line of sec. $K$
(1/4 Sec. and Sec. No.)	(Twp.) San Juan	(Range) (Meridian) New Mexico
(Field)		y or Subdivision) (State or Territory)
he elevation of the der		AILS OF WORK
	DETA ths to objective sands; show sing points, and all  306 1248 3690 3864 4770 4892	
Formation Tops Ajo Alamo Pictured Cliffs Point Lookout Mancos Upper Gallup (Hospah) Lower Gallup Total Depth (Drl Total Depth (Sch	DETA the to objective sands; show sing points, and all 306 1248 3690 3864 4770 4892 ) 5063 1) 5079  work must receive approval ind ad Savings Bldg.	AILS OF WORK  sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement other important proposed work)  Cement plugs will be placed at the following intervals:  290 - 390 1240 - 1300 1590 - 1640 3820 - 3870  Plug at surface to hold in pipe 4 above surface.  By Weldon C. Julander Petroleum Geologist
Formation Tops Ajo Alamo Pictured Cliffs Point Lookout Mancos Upper Gallup (Hospah) Lower Gallup Total Depth (Drl Total Depth (Sch	DETA the to objective sands; show sing points, and all 306 1248 3690 3864 4770 4892 ) 5063 1) 5079  work must receive approval ind ad Savings Bldg.	AILS OF WORK  sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement other important proposed work)  Cement plugs will be placed at the following intervals:  290 - 390 1240 - 1300 1590 - 1640 3820 - 3870  Plug at surface to hold in pipe 4 above surface.