

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

BCO, INC.

3. Address and Telephone No.

135 Grant Avenue, Santa Fe, NM 87501, (505) 983-1228

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

855' FNL, 410' FEL

S13, T24N, R8W; NMPM

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-087657

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Escrito Gallup

8. Well Name and No.

3

Formerly (Smith #2)

9. API Well No.

3004513017

10. Field and Pool, or Exploratory Area

ESCRITO Gallup

11. County or Parish, State

SAN JUAN, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☒ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

NIPPLED UP BOP AND RIGGED UP MUD PUMP. A RETRIEVABLE BRIDGE PLUG AND PACKER WAS USED TO ISOLATE THE CASING FAILURE FROM 2227' TO 2353'. ONE .4" PERFORATION WAS SHOT AT 2350'. THE RETRIEVABLE BRIDGE PLUG WAS SET AT 2500' AND THE PACKER WAS SET AT 1800'. THE CASING FAILURE WAS SQUEEZED WITH 350 SX OF CLASS "B" CEMENT WITH 2% CALCIUM CHLORIDE. THE CEMENT WAS ALLOWED TO SET OVERNIGHT. TRIPPED IN HOLE WITH A BIT AND TUBING AND DRILLED CEMENT FROM 2124' TO 2358'. TRIP IN HOLE TO 2500' AND CIRCULATED HOLE CLEAN TO RBP. TRIPPED OUT OF HOLE AND BACK IN WITH RBP RETRIEVING TOOL AND RETRIEVED THE RBP. TRIPPED IN HOLE AND CIRCULATED HOLE CLEAN TO PBTD AT 5951'. LANDED TUBING AT 5935', RAN ROD PUMP AND RODS AND PUT WELL BACK IN PRODUCTION ON JULY 23, 1993.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title SENIOR FIELD ENGINEER Date AUG 09 1993

(This space for Federal or State office use)

Approved by _____

Title _____ Date AUG 09 1993

Conditions of approval, if any:

FARMINGTON DISTRICT OFFICE