Form	Approved	i.		
Budge	et Bureau	No.	42-R14	24

Form 9-331 6 MMS, 1 File	Form Approved. Budget, Bureau No. 42–R1424				
UNITED STATES  DEPARTMENT OF THE INTERIOR	5. LEASE NM10089				
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME				
(Do not use this form for proposals to drill of to deepen or plag	8. FARM OR LEASE NAME Mary Anne				
1. oil gas well other	9. WELL NO.				
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.	10. FIELD OR WILDCAT NAME Basin Dakota				
3. ADDRESS OF OPERATOR P. O. Box 208, Farmington, NM 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 9, T24N, R9W				
	12. COUNTY OR PARISH 13. STATE San Juan NM				
AT TOTAL DEPTH:	14. API NO.				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	San Juan NM  14. API NO.  14. API NO.  16677 GL  1982  CAUNDER Report results of multiple completion or zone				
REQUEST FOR APPROVAL TO: SUBSEQUENT BEAUTY	1083				
FRACTURE TREAT	CAMBOLA: Report results of multiple completion or zone change on Form 9–330.)				
SHOOT OR ACIDIZE U C C C C C C C C C C C C C C C C C C	CAUNOTE: Report results of multiple completion or zone				
PULL OR ALTER CASING   S. GEOLUGE	Con change on Form 9-330.)				
MULTIPLE COMPLETE  CHANGE ZONES  U  CHANGE ZONES					
ABANDON* XX Spud & Surfac	e Casing				
(other) AX Spud & Sulface	the details and give pertinent dates				

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

385' Drilling - Water. 1/2 degree @ 241'. MI & RU Four 12-23-82 Corners Drilling Co. Rig #10. Spudded @ 11:45 a.m. 12-22-82. Drilled 12½" hole to 241'. Ran 5 jts. 8-5/8" 0.D., 24#, 8Rd, ST&C casing. T.E. 216.35' set @ 228' RKB. Cemented with 135 sacks class "B" plus 2% CaCl (Total slurry 159,3 cu.ft.). P.O.B. @ 4:30 p.m. 12-22-82. Circulate approximately 2 Bbls cement to surface.

Subsurface Safety Valve: Manu. and Type		a de la companya de l	Set @	<u> </u>	_ Ft.
18. I hereby certify that the foregoing is true and signed	d correct TILE Geologist	DATE _	12-23-82		
(This	space for Federal or State	office use)  DATE			
APPROVED BY			Milleprenegi	ngosig Br	

\*See Instructions on Reverse Side