

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator *Bannum Energy*
% Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1710' FSL & 1900' FEL (NW/4 SE/4)
Unit J, Sec. 25, T24N, R8W

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NOO-C-14-20-8452

6. If Indian, Altona or Tribe Name

Navajo

7. If Unit or CA, Agreement Designation

8. Well Name and No.

South Blanco Navajo 25#3

9. API Well No.

30 045 25063

10. Field and Pool, or Exploratory Area

Lybrook Gallup

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to plug as follows:

1. Set cast iron bridge plug 50' above Gallup perforations @ 5450'. Spot Class B cement to cover Gallup top @ 5338'.
2. Perforate 50' below Mesa Verde top @ 3473. Spot 100' Class B cement plug inside and outside casing.
3. Spot Class B + 4% gel cement plug inside casing to cover Pictured Cliffs top 1968' - Fruitland top 1978 - Ojo Alamo 1318'.
4. Spot Class B cement plug from 50' below surface casing @ 276' to surface.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title

Operations Manager

Date

5/25/95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

DISTRICT MANAGER