

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
L2986

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)


1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Kenai Oil and Gas Inc.	8. Farm or Lease Name State of New Mexico 36
3. Address of Operator 717 17th St./Suite 2000, Denver, CO 80202	9. Well No. 12
4. Location of Well UNIT LETTER <u>E</u> <u>1850</u> FEET FROM THE <u>North</u> LINE AND <u>1120</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>24N</u> RANGE <u>8W</u> NMPM.	10. Field and Pool, or Wildcat Lybrook-Gallup
15. Elevation (Show whether DF, RT, GR, etc.) 6856' GL	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled a 7-7/8" hole to 5700'. Ran 5700'KB of 4 1/2" 9.5#, J-55 ST&C casing. Cemented on 1st stage w/500 sxs. Class B 50-50 pozmix w/2% gel 10% salt and .8% D-60. DV tool @ 2115'. Opened DV tool, cemented w/800 sxs. 65-35 pozmix w/6% gel, 1/4#/sk. flocele and 2% CaCl. Tailed in w/100 sxs. 50-50 pozmix w/2% gel, 10% salt and .8% D-60.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Frank T. Chavez TITLE Manager of Operations DATE 11/17/81

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT # 3

APPROVED BY _____ TITLE _____ DATE NOV 19 1981

CONDITIONS OF APPROVAL, IF ANY: