UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEN

SUNDRY NOTICES (Do not use this form for proposals reservoir, Use Form 9–331–C for suc			ON SEL	LS ifferent
reservoir. Use Form 9–331–C for suc	ch proposals.) Proposition	B 00	
1. oil gas well	other	1800 4	S. C. S.	
2. NAME OF OPERATOR Mesa Petroleum Co	•		Oly A	
3. ADDRESS OF OPERATOR				

1660 Lincoln St. #2800, Denver CO 80264

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space AT SURFACE: 820' FNL, 1700' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES

ABANDON*

	NM 12233
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
nt	7. UNIT AGREEMENT NAME
,,,	8. FARM OR LEASE NAME
	South Blanco Federal 26
	9. WELL NO. 5
	10. FIELD OR WILDCAT NAME
	Lybrook Gallup Extension
	11. SEC., T., R., M., OR BLK. AND SURVEY OR
17	AREA
	Sec. 26-T24N-R8W
	12. COUNTY OR PARISH 13. STATE
	San Juan New Mexico
	14. API NO.
E,	
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 68491 GL
E	(NOTE: Report results of multiple completion or zone

5. LEASE

FARIMINGTON, N. M. (other) Production Casing Report 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Subject well was drilled to TD of 5703' on 1/15/82 using a 7-7/8" bit. 139 joints new $4\frac{1}{2}$ " 10.5#/foot K-55 STC production casing and set at 5703'. Float collar located at 5664'. DV tool at 3107'. Cemented first stage with 450 sacks class "B", tailed in with 150 sacks "self-stress". Circulated 5 barrels to the surface. Cemented second stage with 400 sacks 65-35 pozmix, tailed in with 50 sacks Neat. Circulated 10 barrels cement to the surface.

FFB

U. 3 CCOLOGICAL SURVEY

SUBSEQUENT REPORT OF:

APPROVED BY	TITLE DA	ACCEPTED FOR RECORD	_
(Thi	s space for Federal or State office use)		•
18. I hereby certify that the foregoing is true as signed Randa Markovan	TITLE Reg. Coordinator DATE	E 1/28/82	_
18. I hereby certify that the foregoing is true a	nd correct		
Subsurface Safety Valve: Manu. and Type		Set @ Ft	t.
		C+ 0 F	

*See Instructions on Reverse Side

FEB 3 1981

FARMINGTON DISTRICT