

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990 FNL, 990 FEL, Sec. 14, T26N, R3W, N.M.P.M.

A

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

Jicarilla 99

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jicarilla 99 2

9. API Well No.

30-039-06492

10. Field and Pool, or exploratory Area

Gavilan PC/Blanco MV

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Upon further geologic review, our plans have changed to squeeze off excessive water production in the Cliff House as follows:

1. MIRU, TOH
2. Set RBP at 5700'. Set packer at 5200' and squeeze off Cliff House with 200 sx cement. WOC
3. TIH with bit and drill out squeeze cement. TOH. TIH with packer and test squeeze to 500 psi. TOH with RBP & Packer.
4. RU wireline and reperforate Point Lookout from 5776-5900'.
5. TIH with 3 1/2" workstring and packer. Set packer at 5700'. Fracture treat perforations.
6. TOH and lay down workstring.
7. TIH and clean out to PBD, Land tubing at 5900'. Return to production.

14. I hereby certify that the foregoing is true and correct

Signed Vicki Donaghy

Title Production Assistant

Date 12/1/00

(This space for Federal or State office use)

Approved by /s/ Brian W. Davis

Title Lands and Mineral Resources

Date DEC 14 2000

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.