	Form 9-881 b (April 1952)						
		1	6				
			o				
1							

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Appro	Age exhites that on							
Indian Agenc	, Jicarilla							
Apache								
Allottee	*************************							
Leese No.	116							

Budget Bureau No. 42-R359.4.

	·	SUBSEQUENT REPORT OF WATER SHUT-O	FF	X
NOTICE OF INTENTION TO CHANGI	E PLANS	SUBSEQUENT REPORT OF SHOOTING OR	ACIDIZING	
NOTICE OF INTENTION TO TEST W		SUBSEQUENT REPORT OF ALTERING CAS	NG	
NOTICE OF INTENTION TO REDRIL		SUBSEQUENT REPORT OF REDRILLING OF		477
NOTICE OF INTENTION TO SHOOT		SUBSEQUENT REPORT OF ABANDONMENT		<u> V </u>
NOTICE OF INTENTION TO PULL OF NOTICE OF INTENTION TO ABANDO		SUPPLEMENTARY WELL HISTORY		9 1000
				
ÜNDIC	CATE ABOVE BY CHECK MAR	C NATURE OF REPORT, NOTICE, OR OTHER DATA)	11 6 7 70 00	eed. Oo oogo
•		Santanah a 16	in the second se	ده ۱۹۹۵ - سادید ۱۷۳۶ - ساده ۱۷۳۰ - ۲۰۱۳ - ۱۹۳۲ م
Ama al- a	1	September 16	, 19_	9.5
Apache		(N)	<u>.</u>	
Well No	ocated 790 ft. fr	om $\left\{ \begin{array}{l} N \\ S \end{array} \right\}$ line and $\frac{1850}{V}$ from $\left\{ \begin{array}{l} E \\ V \end{array} \right\}$	line of sec. 16	******
NW/4 16	26N	3W NMPM		
(14 Sec. and Sec. No.)	(Twp.)	(Range) (Meridian)		
Blanco Mesaverde		Arriba New M	Mexico	
apicito Pictured Cli	ffs (County	r or Subdivision) (State	or Territory)	
The elevation of the derric	k floor above sea le	vel is 7043 ft. KB	•	
		7031 GL		
	DETA	ILS OF WORK		
State names of and expected depths			licate mudding jobe, con	iont-
	to objective sands; show si ing points, and all	nes, weights, and lengths of proposed casings; in other impertant proposed work)		ient-
pudded 2/2/63. Dri	to objective sands; show at ing points, and all littled 15" hole to	see, weights, and lengths of proposed casings; incorber impertant proposed work) 380. Set 9-5/8" casing a	it 308' KB,	1 4116-
pudded 2/2/63. Dri	te objective sands; show all ing points, and all lled 15" hole to cks of regular	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement ci	it 308' KB, rculated.	ient-
pudded 2/2/63. Dri	te objective sands; show all ing points, and all lled 15" hole to cks of regular	see, weights, and lengths of proposed casings; incorber impertant proposed work) 380. Set 9-5/8" casing a	it 308' KB, rculated.	ient-
pudded 2/2/63. Dri emented with 270 sac rilled 8-3/4" hole to 44 sacks regular thr	te objective sands; show at ing points, and all littled 15" hole to cks of regular o 3950' KB. Se	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement ci	at 308' KB, rculated. emented with	16116-
pudded 2/2/63. Dri emented with 270 sac rilled 8-3/4" hole to	te objective sands; show at ing points, and all littled 15" hole to cks of regular o 3950' KB. Se	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, C	at 308' KB, rculated. emented with	iont-
pudded 2/2/63. Dri emented with 270 sac rilled 8-3/4" hole to 44 sacks regular thr	te objective sands; show at ing points, and all littled 15" hole to cks of regular o 3950' KB. Se	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, C	at 308' KB, rculated. emented with	iont-
pudded 2/2/63. Dri emented with 270 sac rilled 8-3/4" hole to 44 sacks regular thr	te objective sands; show at ing points, and all littled 15" hole to cks of regular o 3950' KB. Se	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, C	at 308' KB, rculated. emented with	
pudded 2/2/63. Dri emented with 270 sac rilled 8-3/4" hole to 44 sacks regular thr	te objective sands; show at ing points, and all littled 15" hole to cks of regular o 3950' KB. Se	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, C	at 308' KB, reulated. emented with d to 1500 psi,	iont-
pudded 2/2/63. Dri emented with 270 sac rilled 8-3/4" hole to 44 sacks regular thr	te objective sands; show at ing points, and all littled 15" hole to cks of regular o 3950' KB. Se	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, C	at 308' KB, rculated. emented with	
pudded 2/2/63. Dri emented with 270 sac rilled 8-3/4" hole to 44 sacks regular thr	te objective sands; show at ing points, and all littled 15" hole to cks of regular o 3950' KB. Se	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, CoC for 12 hours, pressured	at 308' KB, reulated. emented with d to 1500 psi, SEP1 9 1963	Mante-
oudded 2/2/63. Dri emented with 270 sa- rilled 8-3/4" hole to 44 sacks regular thr eld okay.	led 15" hole to cks of regular o 3950' KB. Secough shoe.	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, CoC for 12 hours, pressured	at 308' KB, reulated. emented with d to 1500 psi, SEP1 9 1963	
pudded 2/2/63. Dri emented with 270 sa rilled 8-3/4" hole to 44 sacks regular thr eld okay.	led 15" hole to cks of regular o 3950' KB. Secough shoe.	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, CoC for 12 hours, pressured	at 308' KB, reulated. emented with d to 1500 psi, SEP1 9 1963	iont-
emented with 270 sacrilled 8-3/4" hole to 44 sacks regular threald okay.	led 15" hole to cks of regular o 3950' KB. Secough shoe.	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, CoC for 12 hours, pressured	at 308' KB, reulated. emented with d to 1500 psi, SEP1 9 1963	iont-
pudded 2/2/63. Driver properties of work that the plan of work that this plan of work that the plan of work that this plan of work that the pl	the objective sands; show at ing points, and all illed 15" hole to cks of regular o 3950' KB. Serough shoe. Wo	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, CoC for 12 hours, pressured	at 308' KB, reulated. emented with d to 1500 psi, SEP1 9 1963	
pudded 2/2/63. Driemented with 270 sacrilled 8-3/4" hole to 44 sacks regular threld okay. I understand that this plan of wear the company Consol	the objective sands; show at ing points, and all illed 15" hole to cks of regular of 3950' KB. Serough shoe. Wo	380. Set 9-5/8" casing a with 4% CaCl ₂ . Cement cit 7" casing at 3947' KB, CoC for 12 hours, pressured	at 308' KB, reculated. emented with d to 1500 psi, SEP1 9 1963 OIL CON CONTROL	lent-