Form 9-331 a COPY TO O. C. C.

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe

S.F.079160-A

## UNITED STATES

Unit SW/4 of Sec. 10 is DEPARTMENT OF THE INTERIORDESIGNATED Drilling Unit

APR.

**GEOLOGICAL SURVEY** 

## SUNDRY NOTICES AND REPORTS ON WELLS ARMINE THE P

	<del></del>
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

			March 31,	, 1 <u>53</u>
Well Not	located 990 ft. fr		and 1650 ft. from	ine of sec. 10
SBL SWL Sec. 10  Degle Canyon P. (Ext)	26 N.	7 W.	N.M.P.M.	
Desir CANVON (4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	_
Rio Arriba			New Me	exico
(Field)	(County	or Subdivision)		(State or Territory)

The elevation of the derrick floor above sea level is 6099 ft (Ungraded ground)

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Propose to drill a well with Rotary Tools to the Pictured Cliffs sandstone, set Production casing & test. If production is indicated intend to shoot with Solidified Nitro-gel. Approximate depth 2200 feet.

## CASING PROGRAM:

10-3/4" Csg. at 100', cement with 100 sacks and circulate

5½" Csg. at approx. 2100' with 300 sacks Cement.

I understand that this plan of work must receive approval in writing by th	e Geological Survey before operations may be commenced.
Company KINGSLEY-LOCKE OIL COMPANY	
Address 1400 Luhrs Tower	4
Phoenix, Arizona	By Therego I back
•	Titl-Secretary-Treasurer