

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County Rio Arriba
Initial X Annual _____ Special _____ Date of Test 10-8-63
Company PAN AMERICAN PETROLEUM CORP. Lease Jicarilla Apache 102 Well No. 13
Unit B Sec. 10 Twp. 24N Rge. 4W Purchaser El Paso Natural Gas Company
Casing 4-1/2 Wt. 10.3 I.D. 4.032 Set at 3030 Perf. 7776 To 7790
Tubing 2-3/8 Wt. 4.7 I.D. 1.993 Set at 7742 Perf. - To -
Gas Pay: From 7776 To 7790 L 7783 xG .70 est. -GL _____ Bar.Press. 12
Producing Thru: Casing _____ Tubing X Type Well _____
Date of Completion: 9-30-63 Packer None Single-Bradenhead-G. G. or G.O. Dual _____
Reservoir Temp. _____

OBSERVED DATA

Tested Through PROVER (Choke) PROVER Type Taps Flange

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
1.	7 days					2267		2293		
2.	2 days	3/4 "	140			423		773	60°	
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3630		132	1.000	.9238	1.017	1770
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2305 P_c² 5,313,025

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						616,225	4,696,800		
2.									
3.									
4.									
5.									

Absolute Potential: 1941 MCFPD; n .73

COMPANY PAN AMERICAN PETROLEUM CORPORATION
ADDRESS Box 480, Farmington, New Mexico
AGENT and TITLE F. L. Roberts, District Engineer
WITNESSED By F. W. Foell
COMPANY F. W. Foell ORIGINAL SIGNED BY F. W. Foell

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .