

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Caulkins Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 780, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' F N/L and 1650' F E/L
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Ran Liner

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
Fed SF-079035-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Breech A

9. WELL NO.
127

10. FIELD OR WILDCAT NAME
South Blanco PC

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Section 8 26N 6W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6472' Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 2933' Completed drilling 3-23-52.
3-25-52 5½" OD casing @ 2859' with 200 sacks.
Shot with 482 Qts. SNG 2869'-2933'.
Cleaned out to 2896'. Gas gauged 700 MCF.
4-28-58 Sand water frac'ed with 42,000# sand and 35,196 gallons water.
Daily volume to pipeline after treatment 689 MCFPD.
Daily volume now has decreased to 79 MCFPD to pipeline. It is now proposed to clean out well to 2933' and then cement 2 7/8" liner from approx 2800' to 2933'. Liner will then be perforated opposite PC sand and frac'ed with 50,000 sand. A small pit on existing location will be required to contain frac water after frac job. After job is completed, distured area will be cleaned up and reseeded to within 5' of facilities. Est. starting date July 16, 1979.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles Vergara TITLE Superintendent DATE 7-3-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: