

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
Jicarilla Apache	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry		7. Unit Agreement Name
2. Name of Operator Saxon Oil Company		8. Farm or Lease Name Contract 120
3. Address of Operator 600 First National Bank Bldg., Abilene, Texas 79601		9. Well No. 1
4. Location of Well UNIT LETTER <u>I</u> , <u>790</u> FEET FROM THE <u>East</u> LINE AND <u>1850</u> FEET FROM THE <u>South</u> LINE, SECTION <u>29</u> TOWNSHIP <u>26N</u> RANGE <u>4W</u> NMPM.		10. Field and Pool, or Wildcat Tapacito Assoc. Gallup
15. Elevation (Show whether DF, RT, GR, etc.) 7223' GL		12. County Rio Arriba

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>


17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-8-73 Spud 12 $\frac{1}{4}$ " hole - drill to 223'. Run 8-5/8" csg, set @ 223', cemented w/140 sx cement. Circulate to surface.

1-9-73 Drill 7-7/8" hole to 7538' thru Gallup with rotary tools. Run Induction-Electrolog
to and Densilog.
2-8-73

2-10-73 Spot cement plugs as follows:

7225-7325 - 100'
5400-5500 - 100'
3750-3850 - 100'
3250-3500 - 250'
223 - 50'
10 sx cement top of surface
Well plugged and abandoned.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ernest C. Arnold TITLE Petroleum Engineer DATE 2-22-73

Original Signed by Ernest C. Arnold SUPERVISOR DIST. #3 DATE FEB 26 1973

CONDITIONS OF APPROVAL, IF ANY: