

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
OXY PETROLEUM INC.

3. ADDRESS OF OPERATOR
5000 Stockdale Hwy., Bakersfield, Calif. 93309

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1550'/S, 1530'/E

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SEE ATTACHED



Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED

John Alexander
JOHN ALEXANDER

TITLE AGENT

DATE

06/19/79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

Moved in and rigged up pulling unit on 05/21/79. Perforate Point Lookout 5716-25, 5731-56, 5759-76, 5832-36 and 5860-65, with 1 jet shot per foot. Fractured Point Lookout with 37000 gal. fresh water containing 30 lb./1000 J-2 gel and carrying 55000# 20-40 sand. Sat wireline bridge plug at 5610'. Perforated Menefee 5409-29, 5443-50, 5454-67 and 5492-5506 with 1 jet shot per foot. Fractured Menefee with 39000 gal. fresh water containing 30#/1000gal. J-2 gel and carrying 58000# 20-40 sand. Sat wireline bridge plug at 5310'. Perforated Cliffhouse 5220-37' with 1 jet shot per foot. Fractured Cliffhouse with 11,500 gal. fresh water containing 30#/1000 J-2 gel and carrying 17,000# 20-40 sand. Ran 2 3/8" tubing and retrieved bridge plugs. Ran production tubing and landed at 5563'. Swabbed well in and shut in to wait on pipeline connection. Completion finished on June 5, 1979.