5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990'N, 1790'W AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF SHOOT OR ACIDIZE SHOOT OR ACIDIZ	DEPARTMENT OF THE INTERIOR	Jic Cont. #120
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservor. Use form 9-31-0 for such proposals. 1. oil gas will deepen or plug back to a different reservor. Use form 9-31-0 for such proposals. 2. NAME OF OPERATOR NOTTHMEST Production 3. ADDRESS OF OPERATOR ROX 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 990 M. 1790 N AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOOT OF ACIDIZE BEAR WELL UPLL OR ALFER CASING MULTIPLE COMPLETE CHANGE ZOINE ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all partinent details, and give pertinent dates including estimated date of starting any proposed work. If well its directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Subsurface Casing 117' set at 129'. Cemented w/ 118' cu. ft. cement. Circulate to surface. WOC 12 hours; held 6008/30 minutes.	GEOLOGICAL SURVEY	·
1. oil gas well well other		
well well so other 2. NAME OF OPERATOR 3. ADDRESS OF OPERATOR BOX 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.) AT SURFACE: 990'N, 1790'W AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF RACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE DOPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 29-79: Spudded well. Drilled surface hole. Ran 3 joints of 8 5/8", 24#, KS surface casing 117' set at 129'. Cemented w/ 118' cu. ft. cement. Circulate to surface. WOC 12 hours; held 600#/30 minutes.	4 -1	·i
NOTTHWEST Production 3. ADDRESS OF OPERATOR BOX 289, Farmington, New Mexico 8.7401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990'N, 1790'W AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	well well other	9. WELL NO.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990'N, 1790'W AT TOP PROD. INTERVAL: AT TOPA DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON'* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 29-79: Spudded well. Drilled surface hole. Ran 3 joints of 8 5/8", 24#, KS surface casing 117' set at 129'. Cemented w/ 118' cu. ft. cement. Circulate to surface. WOC 12 hours; held 600#/30 minutes.	Northwest Production	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF SHOOT OR ACIDIZE SHOOT OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 29-79: Spudded well. Drilled surface hole. Ran 3 joints of 8 5/8", 24#, KS surface casing 117' set at 129'. Cemented w/ 118' cu. ft. cement. Circulate to surface. WOC 12 hours; held 600#/30 minutes.	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990'N, 1790'W AT TOP PROD. INTERVAL:	N.M.P.M. 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	·	15. ELEVATIONS (SHOW DF, KDB, AND WD)
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 29-79: Spudded well. Drilled surface hole. Ran 3 joints of 8 5/8", 24#, KS surface casing 117' set at 129'. Cemented w/ 118' cu. ft. cement. Circulate to surface. WOC 12 hours; held 600#/30 minutes. Subsurface Safety Valve: Manu. and Type	TEST WATER SHUT-OFF X FRACTURE TREAT	(NCTE: Report results of multiple completion or zone
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Clerk DATE August 30, 1979	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 29-79: Spudded well. Drilled surface hole. Ran 3 j surface casing 117' set at 129'. Cemented wy	lirectionally drilled, give subsurface locations and it to this work.)* joints of 8 5/8", 24#, KS / 118' cu. ft. cement. Circulate
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Clerk DATE August 30, 1979		
(This space for Federal or State office use)	18. I hereby certify that the foregoing is true and correct	
	18. I hereby certify that the foregoing is true and correct	Set @ Ft. Prk DATEAugust 30, 1979