

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR Curtis J. Little
3. ADDRESS OF OPERATOR P. O. Box 2487
Farmington NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1765'FNL & 1020'FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒ RECEIVED
OCT 4 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or log change on Form 9-330.)



5. LEASE SF-080136
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME SALAZAR
9. WELL NO. #5
10. FIELD OR WILDCAT NAME Ballard PC
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34-T25N-R6W
12. COUNTY OR PARISH Rio Arriba 13. STATE N.M.
14. API NO. 30-039-23059
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6379'GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-28-82 SPUD 2:40 pm 9-28-82. Drld 120'GR of 9-7/8" hole. Ran 119'GR of 7" 23# csg to 120'GR. HOWCO cemented w/65 sx Class B w/2% CaCl & 1/4# floreal (77cf). Cement circulated. Plug down 6:30 pm. WOC 12 hrs. Pressure tested 600 psi. Held OK.
10-2-82 Log TD 2315'GR at 4:00 am 10-2-82. Log Tops: Ojo Alamo 1602, Kirtland 1699, Fruitland 1972, PicturedCliffs 2140, Lewis 2254. Ran 75 jts 2-7/8", 6.5# J-55 to 2296'GR. PBTd 2284'GR. HOWCO cemented w/300 sx 50-50 pos, 6 1/2# gilsonite, 6% gel & 50 sx Class B neat. Total slurry 599cf. Plug down 2:00pm 10-2-82. Pressurized csg to 3500 psi. Held OK.

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Curtis J. Little TITLE Operator DATE October 4, 1982
(This space for Federal or State office use) ACCEPTED FOR RECORD

APPROVED BY _____ TITLE _____ DATE OCT 5 1982
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY smh