

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR Curtis J. Little  
3. ADDRESS OF OPERATOR P. O. Box 2487  
Farmington NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1765'FNL & 1020'FWL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF  
**RECEIVED**  
OCT 08 1982  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE SF-080136  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME SALAZAR  
9. WELL NO. #5  
10. FIELD OR WILDCAT NAME Ballard PC  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 34-T25N-R6W  
12. COUNTY OR PARISH Rio Arriba  
13. STATE N.M.  
14. API NO. 30-039-23059  
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6379'GR

**CORRECTED COPY**

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-28-82 SPUD 2:40 pm 9-28-82. Drld 120'GR of 9-7/8" hole. Ran 119'GR of 7" 23# csg to 120'GR. HOWCO cemented w/65 sx Class B w/2% CaCl & 1/4# floreal (77cf). Cement circulated. Plug down 6:30 pm. WOC 12 hrs. Pressure tested 600 psi. Held OK.  
10-2-82 Log TD 2315'GR at 4:00 am 10-2-82. Log Tops: Ojo Alamo 1602, Kirtland 1699, Fruitland 1972, PicturedCliffs 2140, Lewis 2254. Ran 75 jts 2-7/8", 6.5# J-55 to 2296'GR. PBTd 2284'GR. HOWCO cemented w/300 sx 50-50 pos, 6 1/4# gilsonite, 6% gel & 50 sx Class B neat. Total slurry 599cf. Plug down 2:00pm 10-2-82. Pressurized csg to 3500 psi. Held OK. Cement circulated to surface.

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Curtis J. Little TITLE Operator DATE October 4, 1982

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 15 1982

NMOCC

\*See Instructions on Reverse Side

BY SM