

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Ladd Petroleum Corporation

3. ADDRESS OF OPERATOR
830 Denver Club Bldg. Denver, Colo. 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1700' FSL, 1580' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON*

SUBSEQUENT REPORT TO:

RECEIVED
DEC 06 1982
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE USA FE-079161

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME Lindrith

9. WELL NO. # 24M

10. FIELD OR WILDCAT NAME Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
K Sec. 4-T26N-R7W

12. COUNTY OR PARISH Rio Arriba

13. STATE New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD) 6574' GR

(other) Addendum to cultural resource survey, name change, cubic ft. of cement to be used.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well will be a dual completion in the Dakota and Gallup formation. Two strings of tubing will be run and they will not be comingled subsurface. At the surface, both zones will be metered separately.

We request the name to be changed from the Lindrith # 2-4M to the Lindrith # 24M to comply with New Mexico rules.

Surface casing will be cemented with 225 sxs Class "B" (260 ft³), production casing will be cemented with 450 sxs Class "B" (520 ft³) plus 575 sxs 65/35 Poz (720 ft³).

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Engineer DATE December 2, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
*See Instructions on Reverse Side
JAN 03 1983
OILMCCN. DIV

RECEIVED
DEC 9 1982
James F. Sims
DISTRICT ENGINEER