

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No.1004-035

SUNDEY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen
or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT" For such proposals

Lease Designation and Ser. No

Jicarilla Apache Tribe A118

6. If Indian, Allottee or Tribe Name

Jicarilla Tribe

7. If Unit or CA, Agreement Designat

SUBMIT IN TRIPLICATE

1. Type of Well:

XX Oil Well Gas Well Other

8. Well Name and No.

JAT A118 #10

2. Name of Operator

Apache Corporation

9. API Well No.

3003923556

3. Address and Telephone No.

2855 Southside River Road Suite A, Farmington, NM 87401 505-325-0318

10. Field and Pool, or Exploratory Ar

Tapacito Pictured Cliff

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1760' FNL, 790' FEL, Sec 35, T26N, R3W

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

XX Notice of Intent
Subsequent Report
Final Abandonment Notice

TYPE OF ACTION

XX Abandonment
Recompletion
Plugging Back
Casing Repair
Altering Casing
Other _____
Change of Plans
New Construction
Non-Routine Fracturing
Water Shut-Off
Conversion to Injection
Dispose Water
(Note: Report results of multiple completions on Well Completion or Recompletion Report and LogForm.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any p work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work

Apache Corporation is resubmitting the attached P&A procedures.

00 MAY 15 AM 10:29
JICARILLA APACHE TRIBE
ALBUQUERQUE, N.M.

14. I certify that the foregoing is true and correct.

Signed [Signature] Title Sr Production Foreman Date 5/10/2000

(This space for Federal or State office use)

Approved by [Signature] Title Lands and Mineral Resources Date MAY 10 2000
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly to make to any department or agency to the United States any false, fictitious or
Fraudulent statements or representations as to any matter within its jurisdiction.

All cement – Class B neat 15.6#/gal 1.18 cu ft3 yield.

All spacer fluid – fresh water with 5000 PPM corrosion inhibitor.

1. Drill out cast iron bridge plug @ 4300'.
2. Tag CIBP @ 8100'.
3. Spot 17 sx (20.1 ft3) on top of CIBP.
4. Set CIBP @ 7185'.
5. Spot 17 sx (20.1 ft3) on top of CIBP.
6. Spot 17 sx (20.1 ft3) from 5555' to 5705'.
7. Setting cmt plug across Pictured Cliffs, Kirtland, Ojo Alamo tops:
 - a. Set CIBP @ 4010'.
 - b. Spot 55 sx plug from 3513' to 4010'.
8. Spot 17 sx (20.1 ft3) across Nacimiento from 2537' to 2691'.
9. Pressure test bradenhead to 500 PSI.
 - a. If pressure holds:
 1. Spot 17 sx (20.1 ft3) across surface csg shoe from 216' to 370'.
 2. Fill csg from 60' to surface with cmt.
 - b. If bradenhead can be pumped into:
 1. Perf csg @ 370'.
 2. Circ cmt down 5 ½" csg to surface.
10. Remove wellhead and fill voids w/cmt. Install P&A marker.
11. Remediate location.