## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO D	DRILL, DEEPEN, OR PLUG BACK BACK CAN MENIOD
la. TYPE OF WORK DRILL lb. TYPE OF WELL GAS	5. LEASE NUMBER SF-079160 6. IF INDIAN, ALL. OR TRIBE NAME
2. OPERATOR UNION OIL CO. OF CAL.	7. UNIT AGREEMENT NAME RINCON UNIT
3. ADDRESS OF OPERATOR P O BOX 2074 FARMINGTON, NM, 87401 (505) 325-8786	8. FARM OR LEASE NAME RINCON TOUT 9. WELL NO. # 270
4. LOCATION OF WELL 1658' FNL, 2311' FEL,	10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC.12, T.26N, R.7W,
14.DISTANCE FROM NEAREST TOWN 40 Miles SE of Bloomfield	
15. DISTANCE FROM PROPOSED LOCATION TO NEAREST PROPERTY OR LEASE LINE 1658'	16. ACRES IN LEASE 17. ACRES ASSIGNED TO WELL 320
18. DISTANCE FROM PROPOSED LOCATION TO NEAREST WELL DRILLING, COMPLETED OR APPLIED FOR ON THIS LEASE: 468'	19. PROPOSED 20. ROTARY OR CABLE TOOLS 3089' Rotary
21. ELEVATIONS (DF, FT, GR, E	ETC.) 22. APPROX. DATE WORK WILL BEGIN Spring 1990
23. PROPOSED CASING AN SEE ATTACH	ND CEMENTING PROGRAM HED DRILLING PLAN DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHE WASTE THE PROPERTY.
24. AUTHORIZED BY AGENT	"GENERAL REQUIREMENTS".  DATE
PERMIT NO	APPROVAL DATE
APPROVED BYT	TITLEDATE
NOTE: THIS FORMAT IS ISSUED	IN LIEU OF BLM FORM 316 APPROVED  AS AMENDED
APR2 3 1990	NMOCD APR 18 1990
APR2 3 1990 OIL CON. DIV.	AREA MANAGER

Submit to Appropriate District Office State Lease - 4 copies Fee Lease - 3 copies

330

990

1320

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-102 Revised 1-1-89

CHARTAGO BALLA MEXICO

# OIL CONSERVATION DIVISION

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

· WELL LOCATION AND ACREAGE DEDICATION PLAT DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 All Distances must be from the outer boundaries of the section 2350 Operator RINCON UNIT CO. OF CALIFORNIA UNION OIL County NMPM RIO ARRIBA COUNTY Township Unit Letter R.7 W. T.26 N. G Actual Footage Location of Well: feet from the EAST 2311 1658 NORTH line and Dedicated Acreage: feet from the Pool Ground level Elev. Producing Formation 320 6459 LAND 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interest of all owners been consolidated by communitization, unitization, force-pooling, etc.? MOITIZATION If answer is "yes" type of consolidation □ № If answer is "yes" type of consolidation

If answer is "yes" type of con Yes No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interest, has been approved by the Division. OPERATOR CERTIFICATION hereby certify that the information 5239.08 N 88-16 W and complete to the Printed Name Position 2311 Company Date 5306. SURVEYOR CERTIFICATION SEC I hereby certify that the well location shown on this plat was plotted from field notes of ш actual surveys made by me or under my supervison, and that the same is true and correct to the best of my knowledge and belief. Date Surveyed OIL CON. DIV. Land Surveyor 1000 500 1500 2000 1650 1980 2310 2640

#### RINCON UNIT WELL NO. 270 DRILLING PROGRAM - PAGE 2.

Testing Procedure:
The BOP and related equipment will be tested to 2000 psi in accordance with the provisions of Onshore Oil and Gas Order No. 2.

BOP's will be operationally tested daily, and each test will be logged in the IADC Daily Drilling Report.

## Blooie line:

The blooie line and related equipment will meet all requirements of Onshore Oil and Gas Order No. 2.

#### 4. CASING AND CEMENTING PROGRAM

SURFACE CASING

AGE	<u>Depth</u>	<b>Hole Size</b>	Size	Weight	Grade	Thread
New	0-225'	12-1/4"	8-5/8"	24.0#	K-55	ST&C

INTERMEDIATE CASING

<u>Age</u>	<u>Depth</u>	<u> Hole Size</u>	<u>Size</u>	<u>Weight</u>	<u> Grade</u>	Thread
New	0-TD	7-7/8"	4-1/2"	10.5#	K-55	ST&C

### MINIMUM SAFETY FACTORS

Collapse: 1.0 Tension: 1.8
Burst: 1.0

#### Cementing Program:

- The 8-5/8" surface casing will be cemented to the surface with 175 sacks of class "B" cement with 1. 2% CaCl2 and 1/4# per sack flocele.
- The 4-1/2" production casing will be cemented in 2 stages with the DV tool set at 2900'. 1st stage will be cemented with 85 sacks class "H" cement with .95% Flo-Lock-1, 18% Thrifty Lite, 3% KCL, 3# 2nd stage will be cemented with 325 sacks pacesetter lite with 6% gel,1/3# cello-seal. .8% CF-1, 3# Hi-seal followed with 50 sacks class "C"cement. Actual cement volumes will calculated from open hole logs and will be designed to circulate to surface.

