Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135.
Expires: March 31, 1993

June 1990)	BUREAU OF LAND	MANAC	GEMENT	5. Lease Designation and Serial No.
	•			SF 079302-B
SUNDRY NOTICES AND REPORTS ON WELLS				6. If Indian, Allottee or Tribe Name
and this form for proposals to drill or to deepen or reentry to a different reservoir.				
Use "APPLICATION FOR PERMIT—" for such proposals				
				7. If Unit or CA. Agreement Designation
SUBMIT IN TRIPLICATE				RINCON UNIT
1. Type of Well				
Oil Sas Well Other				8. Well Name and No.
2. Name of Operator				RINCON UNIT #11E
UNION OIL COMPANY OF CALIFORNIA				9. API Well No.
Talanhore No.				30-039-25486  10. Field and Pool, or Expioratory Area
P.O. Roy 2620, Casper, WY 82602 (307) 234-1563 Ext. 116				Basin Dak/S.Blanco
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, State Tocito
2080' FSL & 2410' FEL				Rio Arriba, N.M.
Sec. 6, T26N-R6W	FEL	· •		KIO MITIDO, II Joseph
Sec. 6, 120N-Row			The second second	T OR OTHER DATA
12. CHECK APPE	ROPRIATE BOX(s) TO	INDICA	TE NATURE OF NOTICE, REPOF	RI, OR OTHER DATA
TYPE OF SUBM			TYPE OF ACTION	
TYPE OF SUBM	1551014			Change of Plans
Notice of Intent			Abandonment	New Construction
_			Recompletion Plugging Back	Non-Routine Fracturing
X Subsequent Repo	nc		Casing Repair	Water Shut-Off
			Alterine Casing	Conversion to Injection
Final Abandoni	ient Notice		X Other WEEKLY DRILLING REPORT	Dispose Water
				Completion of Recompletion Report and Logic
	Clearly state all persons	nt details, and	i give pertinent dates, including estimated date of starting kers and zones pertinent to this work.)*	any proposed work. If well is directionally c
13. Describe Proposed or Completed	of measured and true vertical depth	s for all mari	kers and zones perment to this work.)*	
give substitute				
(SEE ATTACHED WEEKLY DRILLING REPORT)				
•				
			and the second of the second o	
			·	
			ME WINDS	SING
			Jun - 5 1935 EV	<u> </u>
			State of the second	
			OM GOOD DAY.	
	•		BUST OF THE	
\		· · · · · · · · · · · ·		
4 hereny certify that the foregon	ing is true and correct		الرياسية	
( )	Serson	Tide _	Drilling Superintendent	Date
This space for Federal or State	office use)			
\		Title		Date
Approved by Conditions of approval, if any:			ACCEPTE	ed for record
14.				

the 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United State 126 (applications) or fraudient state appreciations as to any matter within its jurisdiction.

## RINCON UNIT #11E Rio Arriba County, NM

## Weekly Summary:

- 5-16-95 Fin trip for bit and washed 15' to btm for 5.25 hrs. Drld to 7019' (15.6 FPH). Lost no mud in last 24 hrs. Drilling @ 7116'.
- 5-17-95 TOOH w/bit at 7356'. Drilled to 7338' (13.4 FPH). Drilled to 7356' & started POOH for bit. Lost no mud last 24 hrs.
- 5-18-95 Drld to 7357' (12.6 FPH). TFNB. Repaired rig (3.25 hrs.). Fin POOH w/no drag. TIH to 7285'. Reamed to 7357'. Drld to 7414' (6.1 FPH). No mud lost in last 24 hrs. Operations @ 5:00 a.m. drilling at 7460'.
- 5-19-95 Drld to TD @ 7475'. Made 10 std short trip w/no drag or fill. Circ. POOH. RU loggers. Logger TD 7473'. Ran DIL/GR/SP from 7473' csg & GR to surface. DENS/NEU/GR/CAL/PE from 7473'-2790'.
- 5-20-95 Finished logging. Ran & cmt 175 jts. 7" csg 26# & 23# K-55 csg and tools. Total of 7459' landed @ 7475'. Circ. csg. Cmt in 2 stages. 1st stage- 20 bbl. mud flush, 445 sx 50-50 pos, 4% D112 2% gel, 6.25# Gilsonite, 2# magnifiber/sx, mix at 13.4 ppg, yield of 1.34 cu.ft./in.
- 5-21-95 Cmt 2nd stage w/20 bbl. mud flush, 330 sx 65/35 pos, 12% gel, 3# magfiber, mix at 11.5 ppg, yield of 2.87 cu.ft, followed by 600 sx 50-50 G pos, 4% D112, 2% gel, 6.25# gilsonite, 3# magfiber, mix @ 134 ppg, yield of 1.34 cu.ft. Trail cmt of 175 sx Class G 1.5% B-14 2# magfiber, mix at 15.8 ppg, yield of 1.16 cu.ft. displaced with 198 bbl. water; low 150 psi, high 1800 psi. Bump plug to 2700 psi. Closed DV Tool. Float held OK. Circ. 125 sx cmt to surface. NIP down BOP and clean mud tanks. Set slip, cut off csg and released rig @ 10:00 a.m. 5-20-95. Temp. off report.