UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT ECEIVED

	DI M		
Sundry Noti	ces and Reports on Wells		
	eg 8CT 26 F; 2: 22		
		<i>J</i> .	Lease Number
Marine of Moll	070 17.525.010.1, RM	6.	SF-079302A
Type of Well GAS	ON Palassilian Service	٠. 	If Indian, All. or Tribe Name
		7	Unit Agreement Name
Name of Operator			OHIC AGIEEMENT NAME
-	NOV - 1 1999		
BURLINGTON RESOURCES OIL S			
	or (505) 326-9700 (505)	J\J\3.	Well Name & Number
Address & Phone No. of Operat	or (1) (1) (2) (3) (3) (3) (3)	9.	Kaime #2M API Well No.
FO BOX 4209, Parmington, NM	87499 (505) 326-9700	9.	30-039-26148
Location of Well, Footage, Se	ec., T, R, M	10.	Field and Pool
790'FNL, 955'FWL, Sec.20, T-2	6-N, R-6-W, NMPM		Otero Chacra/
	•		Blanco MV/Basin DK
DUG 0056		11.	County and State
DHC-2256			Rio Arriba Co, NM
. CHECK APPROPRIATE BOX TO IND	CATE NATURE OF NOTICE, REPORT,	OTHER	DATA
Type of Submission	Type of Action		
Notice of Intent		e of Pla	ans
		onstruct	
X Subsequent Report			racturing
	O	C1 (
Final Abandonment	Casing Repair Water		
Final Abandonment	Altering Casing Conver		
Final Abandonment			
Final Abandonment 3. Describe Proposed or Compl	Altering Casing Conver X Other -		
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Ceted Operations O36'. Circ hole clean. TOOH. TIME THE W/166 jts 4 ½" 10.5# J-55 cs. flush, 20 bbl wtr ahead. Cmtd 0.25 pps Flocele, 5 pps Gilson Class "B' cmt w/0.03% defoamer	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
3. Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1 10-23-99 WOC. PT csg to 3	Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other ConverX Other - Altering Casing ConverX Other Other Other Other - But William ConverX Other	H, ran lagg, set w/504 so ite, 0.45% cc trace	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC.
Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. To wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1 10-23-99 WOC. PT csg to 3	Altering Casing Converted Converted Operations 36'. Circ hole clean. TOOH. TIRTH w/166 jts 4 ½" 10.5# J-55 cs flush, 20 bbl wtr ahead. Cmtd 0.25 pps Flocele, 5 pps Gilson Class "B' cmt w/0.03% defoamer 5% retardant (1465 cu.ft.). Cir 8800 psi/15 min, OK. ND BOP. NU	H, ran] sg, set w/504 s nite, 0. c, 0.45% cc trace WH. RD.	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC. Rig released.
3. Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. To wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1 10-23-99 WOC. PT csg to 3 4. Thereby certify that the igned way and way are the signed way.	Altering Casing Converted Converted Operations 36'. Circ hole clean. TOOH. TIRTH w/166 jts 4 ½" 10.5# J-55 cs. flush, 20 bbl wtr ahead. Cmtd 0.25 pps Flocele, 5 pps Gilson Class "B' cmt w/0.03% defoamer 5% retardant (1465 cu.ft.). Cir 8800 psi/15 min, OK. ND BOP. NU	H, ran] sg, set w/504 s nite, 0. c, 0.45% cc trace WH. RD.	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC. Rig released.
3. Describe Proposed or Compl 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. T wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1 10-23-99 WOC. PT csg to 3	Altering Casing Converted Converted Operations 36'. Circ hole clean. TOOH. TIRTH w/166 jts 4 ½" 10.5# J-55 cs. flush, 20 bbl wtr ahead. Cmtd 0.25 pps Flocele, 5 pps Gilson Class "B' cmt w/0.03% defoamer 5% retardant (1465 cu.ft.). Cir 8800 psi/15 min, OK. ND BOP. NU	H, ran] sg, set w/504 s nite, 0. c, 0.45% cc trace WH. RD.	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC. Rig released.
Describe Proposed or Complete 10-21-99 Drill to TD @ 75 10-22-99 Logging. TOOH. To wtr, 20 bbl mud w/3% Econolite, Tailed w/701 sx fluid loss, 0.1 10-23-99 WOC. PT csg to 3 10-23-99 WOC. PT csg to 3 10-23-99 WOC.	Altering Casing Convert X Other - Leted Operations 36'. Circ hole clean. TOOH. TIP TH w/166 jts 4 ½" 10.5# J-55 cs If lush, 20 bbl wtr ahead. Cmtd 0.25 pps Flocele, 5 pps Gilson Class "B' cmt w/0.03% defoamer 5% retardant (1465 cu.ft.). Cir 2800 psi/15 min, OK. ND BOP. NU Foregoing is true and correct. Title Regulatory Administrate Coffice use)	H, ran] sg, set w/504 s nite, 0. c, 0.45% cc trace WH. RD.	ogs. @ 7535'. Pump 20 bbl ex Class "B" neat cmt 1% defoamer (1477 cu.f dispersant, 0.11% cmt to surface. WOC. Rig released.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within the contract of the United States any false, fictitious or fraudulent statements or representations as to any matter within the contract of the United States any false, fictitious or fraudulent statements or representations as to any matter within the contract of the United States and the United States are contracted by the United States and the United States are contracted by the United States are contracted

FARMINGTON FIELD UFFICE