

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

00 NOV -9 AM 10:27

CONFIDENTIAL

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Cougar Com 33

8. Well No.
2

9. Pool name or Wildcat
Basin Dakota

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
McElvain Oil & Gas Properties, Inc.

3. Address of Operator
1050 17th Street, Suite 710, Denver, CO 80265 (505) 325-5220

4. Well Location
Unit Letter C : 790 Feet From The North Line and 2010 Feet From The West Line
Section 33 Township 26N Range 2W NMPM Rio Arriba County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
7484' GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)

SEE RULE 1103.
Spud 12 1/4" surface hole at 12:30 AM, 07/24/00. Drill to 508'. Run 11 joints (488.46") of 9 5/8", 36 ppg, J-55 casing. Casing set at 502' KB. Cement with 300 sacks (354 cf) Class B with 2% CaCl2 and 0.25 pps celloflake. Slurry weight 15.6 ppg. Circulate 15 bbls (72 sacks) good slurry to surface. Plug down at 12:00 AM, 07/25/00. WOC 15 hours. Nipple up BOPE. Pressure test surface casing and BOPE to 600 psi for 10 minutes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R.E. Fielder TITLE Agent DATE 10/13/00

TYPE OR PRINT NAME R.E. Fielder TELEPHONE NO. 505-325-5220

(This space for State Use) **APPROVED BY CHARLIE T. PEREZ**

APPROVED BY DEPUTY OIL & GAS INSPECTOR, DIST. 23 DATE FEB 21 2001

CONDITIONS OF APPROVAL, IF ANY:

X