



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe, N.M.
Lease No. NP 078063
Unit Carson Unit

RECEIVED
OCT 5 1959

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 30, 1959

Well No. 22-30 is located 1890 ft. from N line and 1890 ft. from E line of sec. 30
38 N 30 25E 11E 1890
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Dist 1 San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the Kelly Bushing ~~drill floor~~ above sea level is 6445 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 9-23-59
9-23-59 Ran and cemented (95%) 8-5/8", 24#, 4-55 casing at 105' with 100 sacks to 120 cu. ft. Portland cement, treated with 2% calcium chloride, surface temperature 40°F, formation temperature 75°F, estimated strength after 12 hours 1000 psi. Flanged up and welded on cement. Pressure tested casing and BOP with 500 psi., OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address P. O. Box 158
Farmington, New Mexico

Original signed by
B. W. SHEPARD
By B. W. Shepard
Title Exploitation Engineer

