

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form 7-571 (Rev. 10-1-65)
6. LEASE OR DEED OF THE FEDERAL GOV.

14-20-603-1384

9. IF INDICES, A LOCATION OF TRIBE NAME
Window Rock Indian
Agency

7. UNIT AGENCY NAME

East Bisti Unit

8. FARM OR LEASE NAME

9. WELL NO.

40

10. FIELD AND POOL, OR WILDCAT

Bisti Lower Gallup

11. SEC. T. R. M. OR BLK. AND
SURVEY OR AREA

Section 25-25N-11W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Skelly Oil Company

3. ADDRESS OF OPERATOR

1860 Lincoln Street, Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1882-1320' FNL & 660' FWL Section 25-25N-11W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6552' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☒
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion or plug
Completion or Recompletion Report and Log Form)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of completion of proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and locations pertinent to this work.)*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate.
Plans are to plug and abandon this well; plugging as follows:

First Plug - (5050' - 4950') 100' plug across the Gallup Zone Perfs. 4998-5002'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1285' - 1435') 150' plug extending downward from above the Fruitland
coal section across the Pictured Cliffs SandFourth Plug- (520' - 620') 100' plug extending from 50' above to 50' below the
bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Biles

TITLE

Lead Clerk

DATE

July 16, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side