Form	9-374
(May	19631

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-

GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE.

Budert Burero No. 42 R1424.

14-20-603-1383

С	6. IF INDICES, ALTOUTER OF TRUE SAME
_J 'ent remervoir,	Window Rock-Ma-Des-Pah

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	Window Rock-Pa-Des-Pah	
WELL CX WELL COTHER	Last Bisti Unit	
Skelly Oil Company	8. PARM OR LEADE NAME	
1800 Lincoln Street, Denver, Colorado 80203	9. WELL, NO.	
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIRED AND 1900E, OR WILDCAT Bistl Lower Gallup	
330' FNL & 1650' FEL Section 25-25N-11W	11, REC., T. R., M., OR BLE. AND HURYET OR AREA	
	Section 25-25H-11W	

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH 13, STATE 6587' GR San Juan

Hew Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

TEST WATER SHUT-OFF PULL OR ALTER CASING FRACTORY TREAT MULTIPLE COMPLETE XX SHOOT OR ACIDIZE ABANDON* REPAIR WELL CHANGE PLANS

WATER SHUT-OFF PERMITTED WELL. FRACTURE TREATMENT REPORTING OR ACIDIZING (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and renes pertinent to this work.) *

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable o operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - (5050' - 5150') 100' plug across the Gallup Zone Perfs. 5087-5113'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug'- (1355'-1505') 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (620' - 720') 100' plug extending from 50' above to 50' below too bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

		•		
<u> </u>			111 22 1971	1
SIGNED 6. I hereby certify that the foregoids is true and correct		d Clerk	DIST. 5	¥
(This space for Federal or State office use)			0.51. 5	12.11 <u>12</u>
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE	