

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 070621-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

East Bisti Unit

8. FARM OR LEASE NAME

East Bisti Unit

9. WELL NO.

120

10. FIELD AND POOL, OR WILDCAT

-

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24-29E-11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Supply Well

2. NAME OF OPERATOR

Skelly Oil Company

3. ADDRESS OF OPERATOR

Box 730 - Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

760' FSL & 240' FSL Sec. 24-29E-11W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6537' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐WATER SHUT-OFF ☒REPAIRING WELL ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐FRACTURE TREATMENT ☒ALTERING CASING ☐SHOOT OR ACIDIZE ☐ABANDON* ☐SHOOTING OR ACIDIZING ☒ABANDONMENT* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Well spudded July 10, 1964. Set 16" OD casing at 124' and cemented with 200 sacks by the pump & plug process. Cement circulated to surface. Plug down at 3:00 A.M. July 11, 1964. W.O.C. 24 hrs. Pressured up to 600# for 30 mins. and casing tested OK. Drilled out cement plug and pressured up to 600# for 30 mins. and casing shut off tested OK. Reached total depth of 2640' with 9" hole on July 19, 1964. Reamed 9" hole to 15" hole to total depth. Set 9-5/8" OD casing at 2639' and cemented with 300 sacks by the pump and plug process. Plugged down at 10 A.M. July 20, 1964. Temperature Survey indicated top of cement behind 9-5/8" OD casing at 550'. Tested OK. The 9-5/8" OD casing is slotted with 2' x 1/8" wide slots staggered 4' apart from 2120' to 2639'. A string of 1" tubing was welded to the outside of the 9-5/8" OD casing to a depth of 2383' for treating purposes. Well shut in from July 20, 1964 to December 15, 1964. Moved in and rigged up pulling unit. Ran 8-3/4" bit and drilled out cement from 2045' to 2086'. Circulated and cleaned hole to total depth 2640'. Shut well in from December 16, 1964, thru January 24, 1965. On January 25, 1965, moved in and rigged up pulling unit. Treated through slotted 9-5/8" OD casing from 2120' to 2639' with 2000 gals. 7-1/2% HCL Acid then Acid Water Frac with 2000 gals. 7-1/2% HCL Acid followed by 42,000 gals. water. Ran Roda Series 1-300, 35 Stage on 63 jts. 5-1/2" OD casing as tubing with 1 - 6' pup jt. and set at 2098'. Ran pump at full capacity for one hour and well did not pump off. Continued testing at rate of 9200 bbls. of water per day without pumping off. Well completed in the Mesa Verde (Menefee) Formation.

This well is A Water Supply Well for the East Bisti Unit, which is operated by Skelly Oil Company.

18. I hereby certify that the foregoing is true and correct

SIGNED

(ORIGINAL SIGNED) H. E. Aab

TITLE

Dist. Superintendent

DATE

Feb. 12, 1965


(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

867-551

(REMOVED)