Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SHADDA NULLER WAS DEDUCTE ON MEH 6

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

14-20-603-1349

6. If Indian, Allottee or Tribe Name

Do not use this form for proposals to drill or to deepen or reer Use "APPLICATION FOR PERMIT—" for such	itry to	a different reservoir.
		1 111
SUBMIT IN TRIPLICATE	ψ, ι	the amount of and

NAVAJO-ALLOTTED 7. If Unit or CA, Agreement Designation

1. Type of Well	Di ITONey Nez
Coll Gas Cother Cother	8. Well Name and No.
2. Name of Operator	BISTI LOWER GALLUP #1
W.M. GALLAWAY	9. API Well No.
3. Address and Telephone No. 3005 NORTHRIDGE, SUITE I	30-045-05283
FARMINGTON. NM 87401	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	BISTI LOWER GALLUP
2310' FNL & 2310' FEL (UNIT G)	11. County or Parish, State
SEC. 23, T25N, R11W, NMPM	SAN JUAN CO, NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF AC	TION
Notice of Intent DECEIVED Abandonment	Change of Plans
Recompletion	New Construction
Subsequent Report The FEB 2 1 1995 Plugging Back	Non-Routine Fracturing
Casing Repair	Water Shut-Off
Final Abandonment Notice (0) N D V Altering Casing	Conversion to Injection
Out Golden — Other — — — — — — — — — — — — — — — — — — —	Dispose Water
DIST. 3	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

REASON: WELL IS NOT CAPABLE OF PRODUCING IN PAYING QUANTITIES.

- 1. SET BRIDGE PLUG AT 4625' AND SPOT 25 SKS CEMENT ON TOP
- 2. CLIFFHOUSE CEMENT PLUG INSIDE 5-1/2" FROM 2890' TO 2790' 25 SKS
- 3. PICTURED CLIFFS AND FRUITLAND CEMENT SPOT CEMENT PLUG FROM 1470' TO 1290' INSIDE AND OUT WITH 60 SKS.
- 4. PERFORATE CASING AT 460' ATTEMPT TO CIRCULATE TO SURFACE WITH CEMENT.
- 5. IF CEMENT WONT CIRCULATE, CUT OFF WELLHEAD & RUN 1" DOWN BACKSIDE AT LEAST 50' & CEMENT TO SURFACE INSIDE 8-5/8" CASING & INSIDE 5-1/2" CASING.
- 6. ERECT DRY HOLE MARKER.
- 7. CLEAN LOCATION AND SEED TO SPECIFICATIONS

COMMENT: THIS WELL WAS CEMENT INSIDE WITH 100SKS BY ARCO IN THE CLIFFHOUSE FORMATION ON 11-10-1972

4. I hereby certify that the foregoing is true and correct			
Signed M. M. Salloway	Title OPENATE	مرد	Date 2-7-95
(This space for Federal or State office use)			
Approved by	Title	APPH	OVED
Conditions of approval, if any:	Truc	AS AM	IOVED
		FFR 1	g 1995 -

any department or agency of the United states any larse, flictitious or fraudulent statements Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make or representations as to any matter within its jurisdiction