## SHELL OIL COMPANY

Carson Unit

**Bisti** 

DRILLING REPORT

24

San Juan, New Mexico

(COUNTY)

4-19-59

(SECTION OR LEASE)
T25N R12W
(TOWNSHIP OR RANCHO)

DEPTHS DAY REMARKS FROM Location: 660'S and 660'E of NW Corner Section 24, T25N, R12W, NMPM, San Juan County, New Mexico Elevations: DF 6436.4 GR 6428.9 KB 6437.9 0 2434 Spudded 10:30 A.M., 4-13-59. Ran and cemented (102') 8-5/8" 24#, 4-13 J-55 casing at 112 with 100 sacks cement treated with 2% calcium To chloride. Good returns to surface. Flanged up and waited on 4-14 cement. Pressure tested casing and BOP with 700 psi, O.K. 4-15 2434 4900 Drilled 2466'. To 4-18 4-19 4900 Drilled 115. Ran Electrical Survey and Microlog. Ran and cemented 5015 (5003') 4-1/2", 9.5#, J-55 casing at 5013' with 150 sacks cement (TD) treated with 4% gel. Displaced with oil Final pressure 1800 psi. Released rig 10:30 P. M., 4-19-59. Checked BOP daily Mud Summary WT 9.2-9.7 #1 gal. Vis 43-75 sec. WL 5.2-7 cc. FC 1/32" Contractor: Brinkerhoff Drilling Co. C. Adams Drillers: E. Babcock J. Speaker Company Pusher: R. I. Alberts

	HOLE		CABING SIZE	DEPTH SET
ZE	FROM	то	-	

## SHELL OIL COMPANY

Carson Unit

Bisti (FIELD)

## DRILLING REPORT

24 (SECTION OR LEASE)

San Juan, New Mexico

5-8-59

T25N R12W (TOWNSHIP OR RANCHO)

Jan J	(COUNT				(TOWNSHIP OR RANCHO)			
	(000:::							
DAY			REMARKS					
	FROM	то			/2" holes/ft. 4874-93, 4907-25,			
4-20	5015 (TD)		Perfor 4934-4	ated four 20.6 gram 1 9, 4955-69, 4973-89.	/2 Holes/10. 4011 /09			
4-21			Ran 2-	3/8" tubing to 4982,	packer at 4849', made pressure survey.			
4-22			treatm Pressu pressu minute	ent #1 with 50,000 gare build up from 2250 re 2250 psi, maximum	d. Pulled tubing. Sand oil fracture llons curde, 2#/gal. sand, 320 balls. psi to 2650 psi last 12 minutes. Minimum pressure 2650 psi, average rate 34 bbls/			
4-23 To 4-28			and ro	ods.	, bailed clean, ran pump 2-3/8" tubing			
4-29 To 5-7			Pumpeo	and recovered all lo	oad and frac oil, 1629 bbls.			
5-8			INITIAL PRODUCTION  Pumped 24 hours, 71 B/D gross, 71 B/D gross, 71 B/D clean, cut 0.1%, 40 MCF/D gas GOR 560. Completed 5-8-59.					
		CONDITIO	N AT BEGINN	ING OF PERIOD				
	HOLE			DEPTH SET				
siz 10	FROM		8-5/8"	112'				

CONDITION AT BEGINNING OF 1 211100									
	HOLE		CASING SIZE	DEPTH SET					
SIZE	FROM	то							
12-1/4	' 0	115	8-5/8"	112'					
7-7/8"	115	5015	4-1/2"	5013'					
DRILL	PIPE 4	-1/2"							