

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe, N. Mex.

Lease No. 10007

Unit Artesian Unit

RECEIVED

OCT 5 1959

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 24-11 is located 60 ft. from N line and 198 ft. from E line of sec. 11
24-11 (1/4 Sec. and Sec. No.) 25 (Twp.) 12 (Range) 10007 (Meridian)
1st (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the Kelly Bushing above sea level is 6122 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 9-16-59


9-16-59 Ran and cemented (101') 4-5/8", 24#, J-55 casing at 110'
to with 100 sacks, 122 cu. ft., Portland cement treated with
9-17-59 2% calcium chloride, surface temperature 75°F, formation
temperature 75°F, estimated strength after 12 hours 1000
psi. Flanged up and waited on cement. Pressure tested
casing and BOP with 500 psi, OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operating on the completed.

Company Shell Oil Company

Address P.O. Box 153

Farmington, New Mexico



Original signed by
B. W. SHEPARD

By _____

Title B. W. Shepard
Exploitation Engineer

