

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe, N.M.

Lease No. SF-078066

Unit _____

		15		
X				

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OF REPAIR	
NOTICE OF INTENTION TO PERFORATE AND SAND OIL FRAC.	X	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO PULL OR ALTER CASING			
NOTICE OF INTENTION TO ABANDON WELL			
to Run Casing	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 7, 1956

Well No. 14-15 is located 660 ft. from S line and 660 ft. from W line of sec. 15

SW/4 SW/4 15

25 N.

12 W.

N.M.P.M.

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Bisti

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

Kelly Hushing

The elevation of the ~~surface~~ above sea level is 6251 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Present Status: Depth: 4875'

Surface Casing: 8 5/8" at 219'.

Hole Size: 7 7/8" hole 219' to 4875'.

Proposed Work:

1. Run and cement 5-1/2" casing at 4870' with 200 sacks cement.
2. Clean out to 4840'.
3. Perforate 4 1/2" holes per ft. 4820-4802' and 4792-4780' (29'-116 holes)
4. Sand oil frac. with 30,000 gals oil and 50,000 sand.
5. Set drillable bridge plug at 4782'.
6. Perforate 4 1/2" holes per ft. 4776-4741' (35'-140 holes).

(over)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address 33 Richards St.

Salt Lake City, Utah

By E. W. Shepard

Title Exploitation Engineer

7. Sand oil frac. with 30,000 gals. oil and 50,000#.
8. Set drillable bridge plug at 4735'.
9. Perforate $\frac{1}{2}$ " holes per ft. 4723-4705' (18'-72 holes).
10. Sand oil frac. with 15,000 gals. oil and 23,000# sand.
11. Clean out plugs. Make production test.
12. Install Christmas Tree or artificial lift equipment.