

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe, New Mexico  
Lease No. SF-078062  
Unit Carson

|   |   |   |
|---|---|---|
|   |   |   |
| 1 | 8 |   |
|   |   | X |

SUNDRY NOTICES AND REPORTS ON WELLS

|  |          |  |  |
|--|----------|--|--|
| NOTICE OF INTENTION TO DRILL                   |          | SUBSEQUENT REPORT OF WATER SHUT-OFF        |  |
| NOTICE OF INTENTION TO CHANGE PLANS            |          | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     |          | SUBSEQUENT REPORT OF ALTERING CASING       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL |          | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        |          | SUBSEQUENT REPORT OF ABANDONMENT           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    |          | SUPPLEMENTARY WELL HISTORY                 |  |
| NOTICE OF INTENTION TO ABANDON WELL            |          |  |  |
| <u>Notice of Intention to Refrac</u>           | <u>X</u> |  |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 3, 1963

C. U.  
Well No. 44-18 is located 660 ft. from N line and 659 ft. from E line of sec. 18

SE/4 SE/4 18 25N 11W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Bisti San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the kelly bushing above sea level is 6429.6 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Determine depth of fill from tubing measurement. Clean out to 4950' ± if required.
2. Run tubing with retrievable bridge plug and set plug at 4750' ±.
3. Pressure test casing to 3,000 psi surface pressure.
4. If test satisfactory, retrieve bridge plug. Reset at 4950' ± beneath perforations and pull tubing.
5. Sand-oil frac using 1200 barrels lease crude, 40,000# 20-40 sand and 1000# fluid loss additive. Shut in after oil flush and determine rate of bleed off. (Use 3 Allison for frac.)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address Post Office Box 1200

Farmington, New Mexico

Original signed by  
J. E. DOZIER JR.

By \_\_\_\_\_

Joe E. Dozier, Jr.  
Title Division Production Superintendent

6. Clean out sand above bridge plug with Baker bailer. Run tubing with retrieving tool and retrieve bridge plug. Run tubing with tubing anchor. Run rods and pump.
7. Test well frequently (daily, if possible) and report production rates.