


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe, N.M.
Lease No. 89-673067
Unit Carson



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	X	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 12-14 is located 1920 ft. from N line and 660 ft. from E line of sec. 14
16 25 12 N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Dist 1 San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~rock floor~~ kelly bushing above sea level is 6390 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Status: ID 5033; csg: 8-5/8" 10h', 4-1/2" 5033. Perfs 4560-4964.

Proposed Work for csg. Failure:

1. Determine csg. failure depth.
2. Run tbg. with bridge plug & cementing packer, set cementing packer 300'± above hole in csg. & establish pumping rate & pressure w/cementing truck using water.
3. Mix 200 sx. API Class A cement & pump into csg. Leave approx. 100' of cement above hole in csg. Hold pressure on cement for 4 hrs.
4. Release shoe squeeze tool & pull out of hole. Run tbg. w/3-7/8" bit clean out below hole in csg. w/power tongs.
5. Run swab and attempt to swab fluid down, determining rate of entry.
6. If fluid enters during swabbing, indicating hole is not cemented, repeat steps 2, 3, & 5.

(over)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shell Oil Company

Address Post Office Box 1200

Alamogordo, New Mexico

Original signed by
J. E. DOZIER JR.

By Joe E. Dozier, Jr.
Title Division Production Superintendent

7. If no fluid enters during swabbing, clean out bridge plug to 4964.
8. Run tbgs, rods and pump. Return to pumping production & test until settled rate is established.

(Notified Mr. Arnold with the New Mexico Oil and Gas Commission 3-22-63 and he concurred with plan of work.)