Form	9-331 a
(Feb	. 1951)

1			
ł			
ı	 		
ì		1	
ı		1	1
		1	İ
ı			1
1	 ·		·
1		i	1
	!	i	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	New Mexico	ď
Lease No.	04224	
Unit	Quitzeu	

GPO 862040

TICE OF INTENTION TO DRILL		SUBSEQUEN	T REPORT OF WATER SHUT-	OFF	
TICE OF INTENTION TO CHANGE P		i II	T REPORT OF SHOOTING OR	ACIDIZING	
TICE OF INTENTION TO TEST WATE	ER SHUT-OFF	SUBSEQUEN	T REPORT OF ALTERING CAS	ING.	
TICE OF INTENTION TO RE-DRILL	OR REPAIR WELL	1 11	T REPORT OF RE-DRILLING		1
TICE OF INTENTION TO SHOOT OR		i II	T REPORT OF ABANDONMEN	1	
FICE OF INTENTION TO PULL OR A FICE OF INTENTION TO ABANDON		SUPPLEMEN	TARY WELL HISTORY		
			DY NOTICE OF OTHER DATA		
(INDICA	TE ABOVE BY CHECK MAI	RK NATURE OF REPO	RT, NOTICE, OR OTHER DATA)		eš
		•	December 15	, 19	70
No. 13 is locat	ad 1090 ft fra	m N line ar	nd 990 ft from [I	line of sec	5
		Ser	N.M.P.M.	inic or sec.	
12 Sec. 15 (4 Sec. and Sec. No.)	25 II (Twp.)	(Range)	(Meridian)		
Ballard P.C.	, -,	Trem	Nor N	exico	/E
(Field)		y or Subdivision)	(State	or Territory)	
elevation of the derrick	floor above sea	level is 6680	_ ft.	الج. ۱۰۰ <i>۰ ل</i> و.	5 19 59
	DET	AILS OF WO	RK	.d <u>.</u> • Alecilistis	ochone go N. Den H
names of and expected depths to	o objective sands; show	sizes, weights, and l ll other important p	engths of proposed casings; i	ndicate mudding jobs, cer	ነኝ, ብር <i>ነት</i> (). ment-
	ing points, and a	n other important p	roposca wora,		
To in intended to	olue and aband	ion this wel	l in the follows	ng menuer:	
It is intended to					
l. Spot cement :	olum from 2375	5' to 2175'	v/25 ales. coment		
1. Spot cement ;	plug from 2375	5' to 21.75' a 2256-2286'	v/25 sks. coment		
1. Spot cement prictured Clist 2. Shoot off and	plug from 2375 ffs perf. from d salvage 1856	5' to 21.75' a 2256-2286' 3', 5 1/2" (v/25 sks. coment		
1. Spot cement ; Pictured Clis 2. Shoot off and 3. Cover casing	plug from 2375 ffs perf. from i salvage 1856 stub v/25 ska	5' to 2175' a 2256-2286' 3', 5 1/2" (v/25 sks. coment		
1. Spot cement prictured Cline 2. Shoot off and 3. Cover casing 4. Plug surface	plug from 2375 ffs perf. from d salvage 1850 stub v/25 skr v/10 sks. com	5' to 2175' a 2256-2266' 3', 5 1/2" (a. cessent.	v/25 sks. coment		\
1. Spot cement prictured Cline 2. Shoot off and 3. Cover casing	plug from 2375 ffs perf. from d salvage 1850 stub v/25 skr v/10 sks. com	5' to 2175' a 2256-2266' 3', 5 1/2" (a. cessent.	v/25 sks. coment		
1. Spot cement prictured Cline 2. Shoot off and 3. Cover casing 4. Plug surface	plug from 2375 ffs perf. from d salvage 1850 stub v/25 skr v/10 sks. com	5' to 2175' a 2256-2266' 3', 5 1/2" (a. cessent.	v/25 sks. coment	covering RELEVIO	
1. Spot cement prictured Clim 2. Shoot off and 3. Cover casing 4. Plug surface	plug from 2375 ffs perf. from d salvage 1850 stub v/25 skr v/10 sks. com	5' to 2175' a 2256-2266' 3', 5 1/2" (a. cessent.	v/25 sks. coment	covering RELEVIO	
Pictured Clis Shoot off and Cover casing Plug surface Rect 4' x 4'	plug from 2379 ffs perf. from d salvage 1850 stub v/25 sks v/10 sks. com permanent m	5' to 2175' a 2256-2286' 3', 5 1/2" o a. cement. ment.	v/25 aks. coment	COVERTINE RECEIVED JAN 9 1959 IL CON. COM.,	
Pictured Clis Shoot off and Cover casing Plug surface Rect 4' x 4'	plug from 2379 ffs perf. from d salvage 1850 stub v/25 sks v/10 sks. com permanent m	5' to 2175' a 2256-2286' 3', 5 1/2" o a. cement. ment.	v/25 aks. coment	COVERTINE RECEIVED JAN 9 1959 IL CON. COM.,	d.
Pictured Clis Pictured Clis Shoot off and Cover casing Plug surface Sheet 4 x 4	plug from 2379 ffs perf. from d salvage 1850 stub v/25 sks v/10 sks. com permanent m	5' to 2175' 2256-2266' 3', 5 1/2" 4. cement.	v/25 aks. coment	COVERTINE RECEIVED JAN 9 1959 IL CON. COM.,	d.
Pictured Clii Pictured Clii Shoot off and Cover casing Plug surface Rect 4' x 4' understand that this plan of wor apany Rect 277	plug from 2375 ffs perf. from d salvage 1056 stub v/25 ski v/10 sks. com permanent m	5' to 2175' 2256-2266' 3', 5 1/2" 4. cement.	v/25 aks. coment	JAN 9 1959 IL CON. COM.	d.
Pictured Clin Pictured Clin Shoot off and Cover casing Plug surface Rect 4' x 4' I understand that this plan of wor	plug from 2375 ffs perf. from d salvage 1056 stub v/25 ski v/10 sks. com permanent m	5' to 2175' 2256-2266' 3', 5 1/2" 4. cement.	v/25 aks. coment	COVERTINE RECEIVED JAN 9 1959 IL CON. COM.,	d.
Pictured Clis 2. Shoot off and 3. Cover casing 4. Plug surface 5. Frect 4' x 4' I understand that this plan of wor mpany Box 977	plug from 2375 ffs perf. from d salvage 1056 stub v/25 ski v/10 sks. com permanent me	5' to 2175' 2256-2266' 3', 5 1/2" 4. cement.	v/25 aks. coment	JAN 9 1959 IL CON. COM.	d.
Pictured Clii Pictured Clii Shoot off and Cover casing Plug surface Sheet 4' x 4' understand that this plan of wor apany Box 2077	plug from 2375 ffs perf. from d salvage 1056 stub v/25 ski v/10 sks. com permanent me	5' to 2175' 2256-2266' 3', 5 1/2" 4. cement.	v/25 aks. coment	JAN 9 1959 IL CON. COM. STATE R. G. MILLER	d.