

JAN 8 1956

Budget Bureau 42-R386.1  
Approval expires 12-31-52

APPROVED

(Orig. Sgd.) J. W. LONG

(SUBMIT IN TRIPLICATE)

Land Office Santa FeLease No. NM 04224Unit QuitauUNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Sand Action, New Mexico Treatment

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)


January 7th, 1956

Well No. 9 is located 1171 ft. from N line and 1242 ft. from E line of sec. 11SW/4 SW/4 Sec. 11  
(1/4 Sec. and Sec. No.)25N  
(Twp.)8W  
(Range)N.M.P.M.  
(Meridian)Ballard PC  
(Field)San Juan  
(County or Subdivision)New Mexico  
(State or Territory)The elevation of the derrick floor above sea level is 6991 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

12-27-55 TD 2663'. Sand-oil treated from 2618' to 2663' with 19,780 gallons diesel oil and 25,000# sand, flushed with 2,688 gallons diesel oil. Breakdown pressure 950#, maximum treating pressure 950#, minimum 950# final 550#, injection rate 30 barrels per minute. After 18 hours flowing 4,060 MCF/day. Before treatment 354 MCF/day.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTINAddress 405 1/2 West BroadwayFarmington, New MexicoBy W. E. P. K. K. K.Title Field Superintendent