

Amended

Form 1004-0135  
(June 1993)

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for purposes to drill or recomplete existing wells. Use APPLICATION FOR PERMIT for such purposes.

SUBMIT IN TRIPLICATE

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.  
14-20-60-325

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti Unit

8. Well Name and No.  
29

9. API Well No.  
30-045-05476

10. Field and Pool, or Exploratory Area  
Bisti Lower Gallup

11. County or Parish, State  
San Juan, New Mexico

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
Central Resources, Inc.

3. Address and Telephone No.  
P.O. Box 1247, Bloomfield, New Mexico 87413 (505)-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
1980' FSL, 660' FEL, Sec 8, T25N, R12W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Central Resources, Inc. plugged the well in accordance with regulations. Production equipment was removed and the well was plugged.

December 13-15, 2000

A. Cover top of Gallup plug to 4373' using 18 sacks cement.

B. Cover top of Menefee from 1933' to 1833' using 15 sacks cement.

C. Set Pictured Cliffs plug from 1195' to 1095' inside and outside casing using 51 sacks cement.

D. Place the Fruitland plug from 870' to 770' inside and outside casing using 51 sacks cement.

E. Combine the surface casing shoe plug and the surface plug from 380' to surface to cover the Ojo Alamo interval with 150 sacks.

14. I hereby certify that the foregoing is true and correct

Signed Patty Shelton Title Production Tech. Date December 21, 2000

Patty Shelton

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

FEB 05 2001

\*See Instruction on Reverse Side

OFFICE