

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> <b>Fed.</b> Fee <input type="checkbox"/>
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. State Oil & Gas Lease No.
2. Name of Operator <b>SUNRAY DX OIL COMPANY</b>		7. Unit Agreement Name
3. Address of Operator <b>101 University Blvd., 4th Floor, Denver, Colorado 80206</b>		8. Farm or Lease Name <b>CENTRAL BISTI UNIT</b>
4. Location of Well UNIT LETTER <b>C</b> <b>660</b> FEET FROM THE <b>N</b> LINE AND <b>1980</b> FEET FROM THE <b>W</b> LINE, SECTION <b>8</b> TOWNSHIP <b>25N</b> RANGE <b>12W</b> NMPM.		9. Well No. <b>18</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>6207' K.B.</b>		10. Field and Pool, or Wildcat <b>Bisti Lower Gallup</b>
12. County <b>San Juan</b>		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER **Repair Casing Leak** ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has developed a casing leak. A casing inspection log was run and showed several areas of bad pipe from approximately 3400' to 1500'. We propose to fill up above the perforations with sand. Run 4" OD flush joint pipe to approximately 4775' and cement to above 1400'. The cement plug will be drilled out and the sand washed out. The well will then be returned to production.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **D. E. Hall** *D. E. Hall*

TITLE **District Engineer**

DATE **Feb. 2, 1965**

APPROVED BY *Ernest Chavez*

TITLE **Sup Dist EITB**

DATE **2-4-65**

CONDITIONS OF APPROVAL, IF ANY: