Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT	Expires: March 31, 1993
SONDITO OF EARLD MANAGEMENT	5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS	SF 078063
Do not use this form for proposals to drill or to deepen or contract and different	6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT—" for such proposals	
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well	
Oil Gas Well Other	Carson Unit
2. Name of Operator	8. Well Name and No.
Giant Exploration & Production Company	Carson Unit #21-19
3. Address and Telephone No.	9. API Well No.
P.O. Box 2810, Farmington, NM 87499 (505) 326-3325	30-045-13273
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	10. Field and Pool, or Exploratory Area
and the second s	Bisti Lower Gallup
660' FNL, 1980' FWL, Sec. 19. T25N, R11W	11. County or Parish, State
, and any all was a second and a second a second and a second a second and a second a second and	
12. CHECK APPROPRIATE POWER TO MEDICAL	San Juan County, N.M.
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intel D L G L D L D A L D	
Notice of Interest In the Abandonment	Change of Plans
Subsequent Report 11 IN 2. 4. 1993 Recompletion	New Construction
Subsequent Report JUN2 4 1993 Plugging Back	Non-Routine Fracturing
Casing Repair	Water Shut-Off
Final Abandonm Chice CON. DIV Altering Casing	Conversion to Injection
DIST. 3	_ Dispose Water
13 Describe Pennovad a Combanda	(Note: Report results of multiple completion on Well
Troposed of Completed Operations (Clearly state all pertinent details, and give pertinent details, and give pertinent details, and give pertinent details.	The substitute (choir and rog total)
give subsurface locations and measured and true vertical depths for all markers and account dates, including estimated date of starting	any proposed work if well is directionally drilled
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	ي ن
1	ي ن
1	ي ن
Giant Exploration & Production Company returned the subject well t	o primuction astfollows:
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49	o primuction astfollows:
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.	o production as follows:
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line	o production as follows:
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and numbed 200 sks (77/4)	o production astfollows:
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane	o primuction as follows:  45'. Clayed dewn  r at 482:  cu 12' cement  flakes following
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk	o production as follows:  45'
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl <sub>2</sub> and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi	o production as follows:  45'
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl <sub>2</sub> and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.	o production as follows:  45'. Layed dewn  r at 4482: cu coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl <sub>2</sub> and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f	o production as follows:  45'. Dlayed dewn  r at 482: cu to coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49	o production as follows:  45'. Dlayed dewn  r at 482: cu to coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl <sub>2</sub> and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.	o production as follows:  45'. Dlayed dewn  r at 482: cu to coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.	o production as follows:  45'. Dlayed dewn  r at 482: cu to coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.	o production as follows:  45' Layed dewn  r at 4482: cu 22 coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on	o production as follows:  45' Layed dewn  r at 4482: cu 22 coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl <sub>2</sub> and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.	o production as follows:  45' Layed dewn  r at 4482: cu 22 coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.	o production as follows:  45'. Dlayed dewn  r at 482: cu coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and  June 18, 1993
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.  14. Thereby certify that the foregoing is true and correct  Applications Title Vice President of Operations	o production as follows:  45'. Layed dewn  r at 482: cu
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.	o production as follows:  45'. Dlayed dewn  r at 482: cu coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and  June 18, 1993
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.  14. Thereby certify that the foregoing is true and correct  Signed  Title Vice President of Operations  Title Vice President of Operations	o production as follows:  45'. Layed dewn  r at 4482: cu & coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and  June 18, 1993  Date  Date
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.  14. Thereby certify that the foregoing is true and correct  Signed  Title Vice President of Operations  Title Vice President of Operations	o production as follows:  45'. Layed dewn  r at 482: cu
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.  14. Thereby certify that the foregoing is true and correct  Signed  Title Vice President of Operations  Title Vice President of Operations	o production as follows:  45'. Layed dewn  r at 4482: cu & coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and  June 18, 1993  Date  Date
Giant Exploration & Production Company returned the subject well t  1. Circulated hole clean with 2-3/8" tubing to a depth of 49 2-3/8" tubing.  2. Ran 149 jts of 3-1/2", 8.81# flush joint liner. Set line Cemented liner as follows: mixed and pumped 200 sks (774 containing 3% sodium metasilicate and 1/4#/sk cellophane 100 sks Class "B" cement containing 2% CaCl2 and 1/4#/sk Squeezed bradenhead with 50 sks Class "B" cement containi 1/4#/sk cellophane flakes.  3. Drilled out cement. Pressure tested casing to 1000 psi f 4. Acidized existing perforations (4866' - 4892', 4900' - 49 4939' - 4944') with 1000 gallons of 15% HCl.  5. Ran a 2-1/16" tubing string. Ran rods and pump.  This well had first production to the Carson Unit tank battery on at 1:45 pm.  14. Thereby certify that the foregoing is true and correct  Signed  Title Vice President of Operations  Title Vice President of Operations	o production as follows:  45' Layed dewn  r at 4482: cu & coment flakes. Tailed in with cellophane flakes. ng 2% CaCl <sub>2</sub> and  or 15 minutes. Held. 08', and  JUN 2 1 1993  Date  Date

RY \_\_\_\_\_SW^ \*See Instruction on Reverse Side